



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11683 - 13W LED 6" Round Slimfit Performer Series 12PK; 90 CRI 27/30/35/40/50 CCT; White Flat; Dimming 120V input; Must Order in Multiples of 12

- Air Tight
- Flicker Free
- CCT Selectable
- IC Rated



ELECTRICAL

Technology:	LED
Watts:	13W
Volts:	120V
Lumens:	1100L
Lamp Base :	Integrated - Integrated
Efficacy:	84.62 LPW
CRI:	90+
CCT (Kelvins):	27K/30K/35K/40K/50K - Warm White to Natural Light
Beam Spread :	110
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Forward (TRIAC) or Reverse Phase; 120V only
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Phase Cut (TRIAC); 120V only
Incandescent Equivalent :	75W
Operating Temperature :	-4F to +104F (-20C to +40C)
Lamp Included :	Integrated
Replaceable Light Source :	No
Connection:	Hardwire
Surge Protection :	Built-in-surge protection - 0.5KV
THD:	<20%
Power Factor :	>0.9
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923116834
Each Quantity:	1
Each Dimensions:	19.29 x 12.05 x 7.40

INFO

Additional Info:	Must Order in Multiples of 12
Specification Note:	Must Order in Multiples of 12
Includes:	3pcs wire nut

PHYSICAL

Fixture Type:	Miniature
Finish:	White
Lens Finish:	Frosted
Lens Material:	Plastic (PS)
Dimensions:	H:1.75" DIA:6.79"
Weight (Lbs.):	0.88
Material:	Plastic (PS)

INSTALLATION

Ceiling Aperture:	6.34 in. cutout
Max Drywall Thickness:	1.181 in.
Clearance Height:	3.54
Sloped Ceiling Compatible:	No

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	4528769
Energy Star Lamp Category:	Downlight Recessed
CA Prop 65:	Lead
BAA Compliant:	No
Closet Rated:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES

	80-866	6-Inch Asymmetric New Construction Recessed Downlight Mounting Plate; Flat
	80-867	Universal New Construction Recessed Downlight Mounting Plate; Flat; 3.5-Inch; 4-Inch; 6-Inch; 8-Inch
	80-944	New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/Joist mounting of 6-inch Recessed Downlights; Up to 6.25-inch hole diameter
	80-952	New Construction Mounting Plate for Stud/Joist mounting of 6-inch Recessed Downlights; Up to 6.5-inch hole diameter
	80-985	6 FOOT REMOTE DRIVER 3-PIN EXT
	80-997	Downlight Hanger Bar Kit; For Asymmetrical Plates; New Construction