

# Ensemble™

# A KOHLER COMPANY 60" tile shower wall set w/Aging in Place backerboards

# 71124106

#### **Features**

- Complete 3-piece backed wall set.
- Made from solid Vikrell® material for strength, durability, and lasting beauty.
- Durable high-gloss finish provides a smooth, shiny surface that is easy to clean.
- Tongue-and-groove interlocking joints form a seamless appearance and simplify installation.
- Modular design allows it to be moved around corners and through doorways with ease.
- Realistic tile look.
- Features convenient shelving.
- Includes age in place factory installed backers for later grab bar installation.



### **Recommended Products/Accessories**

5325EZ-59 Frameless sliding bath door 5425-59 Frameless sliding bath door 5427-59 Frameless sliding bath door 542808-59 Frameless sliding bath door 80001012 12" straight grab bar 80001018 18" straight grab bar 80001024 24" straight grab bar 80011032 32" straight grab bar 80001036 36" straight grab bar

#### Codes/Standards

CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662

# Warranty – Bathing Fixtures (and) Kitchen and Utility Sinks Made of Solid Vikrell® Material

See website for detailed warranty information.

## Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	KOHLER Biscuit





# Ensemble™

# 60" tile shower wall set w/Aging in Place backerboards

No image available. This product is a component and not intended to be a standalone installation.

#### **Technical Information**

All product dimensions are nominal.

Installation: Three-wall alcove

#### Notes

Install this product according to the installation instructions.

Product is designed to be used with a single-hole mixer valve with an escutcheon cover not to exceed 7-3/4" (197 mm) in width.

Bath cannot be installed without the wall surround.

Width of back wall at top transitions from 60" (1524 mm) at the front to 59-3/8" (1508 mm) in the back corners. Furring strips approximately 1/4" (6 mm) thick should be used at the back corner studs if drywall is to be installed over the nailing flange.