


# HR-2LED-T209N

2" Tesla™ LED Shower Trim

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

## PRODUCT DESCRIPTION

Minimum profile, round shower trim with interior open reflector.

## FEATURES

- 2" aperture
- CEC Title 24 Compliant (90CRI model)
- Wet location listed
- 30° visual cutoff angle for glare control
- 90,000 hours rated life
- 5 year WAC Lighting product warranty

## SPECIFICATIONS

**Construction:** Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

**Light Source:** Utilizes one 14.5W LED, CRI: 85 & 90+

**Dimming:** 0-10V Dimming: 100%-10%  
ELV Dimming: 100%-15% (120V only)

**Mounting:** Two heavy gauge retention clips hold trim firmly to housing

**Finish:** White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

**Standards:** ETL & cETL Listed. Wet location listed.

See table below for California Title 24 Compliant for qualifying products.

## TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	2013 Title 24	Finish
<b>HR-2LED-T209N</b> <i>Shower Light</i> <i>Wet Location Listed</i>	26°	<b>27</b> 2700K	85	475	1401	No	<b>BN</b> <i>Brushed Nickel</i> <b>CB</b> <i>Copper Bronze</i> <b>WT</b> <i>White</i>
		<b>W</b> 3000K	85	510	1535	No	
		<b>9W</b> 3000K	90	528	1615	Yes	
		<b>35</b> 3500K	85	535	1616	No	
		<b>C</b> 4000K	85	485	1531	No	

**HR-2LED-T209**

**N**

-

-

Example: HR-2LED-T209N-9W-BN

**COMPATIBLE HOUSINGS** See individual housing spec sheets for complete information.

Model	Input	Notes
<b>HR-2LED-H09D-ICA</b>	120V -277V	Ceiling thickness: ½" -¾"
<i>New Construction</i> <i>IC-Rated, Airtight</i>		
<b>HR-2LED-H09D-ICAC</b>	120V -277V	Requires 3" of clearance from insulation on all sides
<i>New Construction</i> <i>IC-Rated, Airtight</i> <i>Chicago Plenum</i>		
<b>HR-2LED-R09D-A</b>	120V -277V	Ceiling thickness: ½" -1"
		<i>Remodel</i> <i>Non-IC, Airtight</i>

## REPLACEMENT MODULES

### Reflectors

<i>Spot</i>	<b>SL-REF-LUX10-S</b>
<i>Narrow Flood</i>	<b>SL-REF-LUX10-N</b>
<i>Flood</i>	<b>SL-REF-LUX10-F</b>

### LED

2700K	85 CRI	<b>LXS8-PW27</b>
3000K	85 CRI	<b>LXS8-PW30</b>
3000K	90 CRI	<b>LXS9-PW30</b>
3500K	85 CRI	<b>LXS8-PW35</b>
4000K	85 CRI	<b>LXS8-PW40</b>

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760