



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11713 - 9 watt LED Direct Wire Downlight; Gimbaled; 6 inch; 3000K; 120 volt; Dimmable

- Air Tight
- IC Rated



ELECTRICAL

Technology:	LED
Watts:	9W
Volts:	120V
Lumens:	720L
CRI:	90
CCT (Kelvins):	3000K
Temperature:	Warm White
Beam Spread :	90
Hours Rated:	40000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable or Triac
Incandescent Equivalent :	65W
Operating Temperature :	-20C (-4F) to +40C (+104F)
Replaceable Light Source :	No
Connection:	Direct Wired
Power Factor :	>.9
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923117138
Each Quantity:	1
Each Dimensions:	6.93 x 4.25 x 6.93
Case UPC:	10045923117135
Case Quantity:	12
Case Dimensions:	14.57 x 13.39 x 14.76

INFO

Specification Note:	Aiming Angle: 30dg
Min Compartment Size:	Height: 4.72 in.

PHYSICAL

Finish:	White
Finish Family:	White
Dimensions:	W:6.69" H:3.69"
Weight (Lbs.):	0.72
Material:	Aluminum / Polycarbonate (PC)

INSTALLATION

Ceiling Aperture:	5.70 in. Cutout
Max Drywall Thickness:	1-1/8 in.
Sloped Ceiling Compatible:	Yes

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Energy Star Qualified:	No
UL/ETL Application:	Ceiling
CA Prop 65:	Lead
NOM Certificate No.:	NTEC21EL007844
NOM Expiration Date:	12/29/2022
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES



80-947 6" Goof Ring for Remote Driver Installation



80-951 Rough-In Mounting Plate; 6" with Junction Box

DIMMER COMPATIBILITY

Leviton 66ELV

Satco 86/103

LeGrand ADTP703TU

Lutron CTRP-253P

Cooper DALo6P-C2

Lutron DVLV-600P

Lutron DVRP-253P

Leviton DW6HD

Leviton IPEo4-1L

Leviton IPLo6

Lutron MA-PRO

Lutron NTCL-250

Lutron NTRP-250

Cooper SALo6P

Lutron SLV-600P

Cooper SUF7

Cooper TALo6P-C2
