


HR-802

2.5" Low Voltage New Construction Housing

120V – Non-IC – Electronic

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

120V input, non-IC new construction housing with electronic transformer. For use with 2.5" low voltage trims.

FEATURES

- Cutout: 3"
- Integral Electronic Transformer
- Advanced auto-reset, soft start and short circuit protection
- 3" clearance on all sides when insulation is present
- Suitable for chain wiring
- J-box and transformer accessible through ceiling opening
- Suitable for damp locations
- UL and CUL Listed

ORDER NUMBER

HR-802

SPECIFICATIONS

Construction: Housing and junction box are 20 gauge steel, painted black. Frame and hanger bars are heavy gauge galvanized steel. Electrical component within can is a bi-pin ceramic socket with 18 gauge teflon insulated wires with fiberglass sleeves.

J-Box: Three 1/2" knockouts provided for wire entry and exit. Suitable for chain wiring.

Transformer: Electronic transformer for 12V MR16 lamps, 50W maximum. 120V input transformer, 1W minimum load.

Dimming: 100%-10% Electronic Low Voltage(ELV) Dimming

Mounting: Supplied with hanger bars, adjustable from 12"-24" to accommodate various joist construction and grid sizes. Hanger bars have slots for easy mounting on "T" bars. 3" cutout hole. Handles mounting surface thickness up to 3/4".

Rating: Non-IC: insulation must be kept at least 3" away from the housing.

Standards: UL & CUL Listed

COMPATIBLE TRIMS

Model #	Description	Finish – (where there is a slash (/) the letters correspond as: interior finish/exterior finish)
HR-834	Metal Trim Step Baffle	Black/White (WT), White/White (WT/WT)
HR-836	Metal Trim Downlight	Brushed Nickel (BN), Copper Bronze (CB), White (WT)
HR-837	Gimbal Ring 25° Adjustment from Vertical	Black (BK), Brushed Nickel (BN), Chrome (CH), Copper Bronze (CB), White (WT)

See individual trim spec sheets for complete information.

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585