



Assembly Instruction Sheet

Package Contents

| Part | Description | Quantity |
|------|----------------|----------|
| A | Crossbar | 1 pc. |
| B | Ceiling Canopy | 1 pc. |
| C | Fixture Arm | 4 pc. |
| D | Metal Frame | 4 pc. |
| E | Frame Cover | 4 pc. |



STEP 1

Remove the Crossbar(A) from the Ceiling Canopy(B). Assemble the Fixture Arm(C) with the Canopy(B).

STEP 2

Assemble the Metal Frame(D) to the Fixture Arm(C). Insert your bulb to the bulb base.

STEP 3

Attach the Frame Cover(E) to the Metal Frame(D). Clamp the Frame(D) and the Cover(E) together with the 2 clips on the Cover(E).

STEP 4

Feed the supply wires through the Crossbar(A). Screw the Crossbar(A) against the ceiling.

STEP 5

Twist the 6 black wires together as one. So do the 6 white ones. Connect one Supply Wire to the black wires from the fixture. Connect the other Supply Wire to the white wires from the fixture. Connect the Ground Wire to the yellow wire from the Canopy(B).

STEP 6

Attach the Canopy(B) to the Crossbar(A). Tighten the cap nut against the Canopy(B) to secure in place.

Your fixture is now assembled and ready to use.