

JJFTYI-000300

Specification

Material: 304 Stainless Steel
Color: Silver
Process: Brushing
Style: Modern
Installation Required: Yes
Mounting Type: Faucet Mount
Inlet Water Pressure: 0.2-0.4MPa
Work Pressure: 15-100psi
Purified Water Flow Rate: 0.5L/0.13gal/min
Working Temperature: 5-38 °C/41-100.4°F
Product Length: 130mm/5.12in
Filter Element Size(D*H): 40*93mm/1.57*3.66in
Package Size: 21.5*18*7.5cm/8.46*7.09*2.95in
Gross Weight: 0.87kg/1.92lbs
Net Weight: 0.83kg/1.83lbs



Package Included

1* Faucet Water Filter
4* Filter Elements
1* English&Chinese Manual
Other Accessories for Assembly

How to Use

1. First, unscrew the bubbler on the original faucet and find the appropriate adapter for the faucet.
2. Place a rubber gasket into the appropriate adapter to prevent water leakage.
3. Remove the protective film from the filter element and install it. Tighten the faucet to allow water to flow.

Application

This product can be used in kitchens, bathrooms, pet drinking water, RVs, etc.

Notes

1. Please read the operating manual completely before use. And pay particular attention to the safety instructions included.
2. This product will not reduce the TDS value due to the presence of minerals in water. If you want to reduce the TDS value, please choose the Waterdrop RO mechanism.
3. This product cannot be used for square and irregular-hole water faucets.
4. Please allow the slight color difference caused by the shooting light and 1-3cm error due to manual measurement, and make sure you do not mind before ordering.