

ASSEMBLY INSTRUCTIONS



CAUTION

◆ Inspect the wire insulation for any cuts, abrasions, or exposed copper that may have resulted during shipping. If there is a defect in the wire, do not attempt installation.

◆ Before starting installation of this fixture or removal of a previous fixture, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.



If you need further assistance, please contact us

TOOLS REQUIRED



Ladder



Safety glasses



Electrical tape




Phillips screwdriver



Flat blade screwdriver




Pliers



Wire strippers


HARDWARE INCLUDED



Fixture




Glass Shade



Cage



Fixture Screws



Mounting Unit




Mounting Screws



Wire Nuts

*PARTS SHOWN MAY DIFFER SLIGHTLY PER LIGHT FIXTURE


EXPLODED PARTS



INSTALLATION


STEP 1

Use the **mounting screws** to attach the **mounting unit** to the junction box (not included).





STEP 2

Disassemble the **Cage** and **Glass Shade** under the **fixture** by unscrewing screws.




STEP 3

Make the electrical connection from the junction box (not included) to the **fixture**. Connect the ground wire to the **mounting unit** using the preinstalled green ground screw. Next, connect the live wire, neutral wire and ground wires with the supplied **wire nuts**. Secure with electrical tape.




STEP 4

Attach the **fixture** to the **mounting unit** by inserting two **fixture screws** and rotating the **fixture** until it locks in place. Then tighten the **fixture screws** securely.



STEP 5

Select the color temperature you need.



STEP 6

Use the **screws** to attach the **Glass Shade** and **Cage** to the **fixture**.

