



General Information

Material number

Type	recessed light
Product segment	Indoor
Theme	EGLO connect.z
FSC®	FSC® Mix70% Hevea br FSC® C152762

Dimensions

Article Height (in mm)	310
Article Length (in mm)	225
Net Weight (in kg)	0.44 Kilogram
Article Overhang (in mm)	85
Article Width (in mm)	135
Article Diameter (in mm)	216
Canopyens længde (i mm)	400
Canopyens bredde (i mm)	45
Canopyens højde (i mm)	45
Base Diameter (in mm)	160
Base Length (in mm)	240
Base Width (in mm)	160
Installation Depth (in mm)	26
Cutout (in mm)	205

98842

FUEVA-Z

Material & Colour

Enclosure Material	aluminium
Enclosure Colour	white
Glass/Shade Material	plastic
Glass/Shade Colour	white
Cable Colour	textil-cable black

Functionality

Switch Type	without switch
Battery	No
Function	control via APP + remote control CCT
Battery Type	Li-ion; 1200mAh
Sensor Angle (in °)	120
Sensitivity min. (in lux)	30
Burning Time min. (in sec.)	5
Burning Time max. (in sec.)	15
Distance (in Meter)	6

Technical Information

Protection Degree	IP20, IP44
Protection Class	2
Mains Voltage	220-240V,50/60Hz
Operation Voltage	220-240V,50/60Hz
max. Wattage (1)	16,5W
Dimmable	Yes
Spannung	220-240V 50/60Hz
U out	46-70V
I out	300mA
Hz	100Hz

Illuminant 1

Illuminant Type (1)	E27
Illuminant incl. (1)	Exclusive
Socket Type (1)	E27

Illuminant 1

Socket Type (1)	LED
Illuminant Type (1)	LED
Illuminant incl. (1)	Inclusive
Kelvin Complete	2700-6500K
Light colour Complete	TUNEABLE WHITE
Nominal Lifetime (in h)	5000
Tænd-/slukcyklusser	15000
Energy efficiency class (EEI)	E
Dimmable	Yes
Info changeability□light source/driver	LED + driver cannot be exchanged
Lyskildens faktiske effekt (0,1 W præcision)	18
Farvetolerance (LED, SDCM)	<6
Lumen Complete	2100

Illuminant 1

Socket Type (1)	GU10
Illuminant Type (1)	GU10-LED
Illuminant incl. (1)	Inclusive
Energy efficiency class (EEI)	F
Info changeability□light source/driver	LED exchangeable by customers, no driver included

