



Tresham® | K-1974

48" x 36" single-threshold center drain shower base

Features

- Low-threshold design for easy entry and exit
- Single threshold for three-wall installation
- Coordinates with other products in the Tresham collection



Codes/Standards

CSA B45.5/IAPMO Z124
ASTM E162
ASTM E662

Technical Information

All product dimensions are nominal.

Drain Location:	Center
Drain Hole Diameter:	3-3/8" (86 mm)
Minimum Floor Load:	20 lbs/ft ²
Weight:	52 lbs (23.6 kg)

Material

- Acrylic

Recommended Products/Accessories


K-23726 Drain treatment
K-23732 Tub & shower cleaner
K-9132 Round shower drain for use with plastic pipe, gasket included
K-706008-D3 43-5/8"-47-5/8" W x 74" H bypass shower door with 1/4"-thick Frosted glass
K-706008-L 44-11/16"-47-5/8" W x 74" H bypass shower door with 1/4"-thick Crystal Clear glass
K-706010-L 44-5/8"-47-5/8" W x 74" H sliding shower door with 3/8"-thick Crystal Clear glass
K-706011-L 44-5/8"-47-5/8" W x 82" H sliding shower door with 3/8"-thick Crystal Clear glass
K-706014-D3 44-5/8"-47-5/8" W x 74" H bypass shower door with 1/4"-thick Frosted glass
K-706014-L 44-5/8"-47-5/8" W x 74" H bypass shower door with 1/4"-thick Crystal Clear glass
K-706016-L 44-5/8"-47-5/8" W x 74" H sliding shower door with 3/8"-thick Crystal Clear glass
K-706017-L 44-5/8"-47-5/8" W x 82" H sliding shower door with 3/8"-thick Crystal Clear glass

Warranty

See website for detailed warranty information.

KOHLER® Plastic Baths and Receptors Lifetime Limited Warranty





Installation

- Center drain

Installation Notes

Install this product according to the installation instructions.

Measure your actual product for rough-in details.

Shimming may be required between the stud frame and the fixture.

Stud opening tolerance is +1/4" (6 mm), -0" (0 mm).

KOHLER steam generator/control kit are designed for use with this product. Kohler Co. shall not be responsible for problems encountered due to the installation and use of other manufacturer's steam generators.



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.

7-29-2026 20:30 - US-CA