






TASSEL PENDANT

ASSEMBLY INSTRUCTIONS




PARTS LIST & HARDWARE LIST

| LABEL | DESCRIPTIONS | PICTURE | QTY |
|-------|----------------|--|-----|
| A | MOUNTING plate |  | 1X |
| B | CANOPY |  | 1X |
| C | WIRE CONNECTOR |  | 2X |
| D | SCREW |  | 2X |

PREPARATION

WE RECOMMEND INSTALLATION BY A LICENSED ELECTRICIAN.
This fixture has been rated for up to 60-watt maximum TYPE A bulbs.
To avoid the risk of fire, do not exceed the recommended wattage.




WARNINGS:

All wires are connected. When unpacking, be careful not to pull wires as a bad connection may result. Do not connect electricity until your lamp is fully assembled.

To reduce the risk of fire, electrical shock, or personal injury, always turn off lamp and allow it to cool prior to replacing light bulb.

Do not touch bulb when fixture is turned on or look directly at lit bulb.
Keep flammable materials away from lit bulb.

Step 1



TO ASSEMBLE:

1. Carefully remove all parts from the box and remove all plastic covering.
2. Turn OFF power to the junction box where the lamp will be installed.
3. If need, disassemble the existing suspension tube 2(K) by unscrewing the sections apart. Pull the wire back through the canopy section that will be need to be extended. Locate the Extension tubes(L) and check the actual suspension length conditions to the incremental fixture suspension length per number of extensions desired.
4. Attach the ground wire from the fixture to the ground junction box wire from the outlet box (Usually green or bare wire). Or wrap the fixture's ground wire around green ground screw (b), and then fix the green ground screw into the mounting plate (A).
5. Connect the hot wire to the hot junction box wire (usually black or smooth) with a plastic wire connector(a) and wrap the connection with electrical tape. Connect the neutral wire to the neutral junction box wire (usually white or ribbed) with a plastic wire connector(a) and wrap the connection with electrical tape.
6. Fasten mounting plate (A) onto the ceiling outlet box using two mounting screws (c).
7. Attach the Canopy(B) to the mounting plate (A).
8. Insert the 60-watt bulbs (included) into threaded sockets.
9. Restore power to the junction box and test lamp fixture.
10. Installation is complete.

Step 2

CARE & MAINTENANCE

Do not use polishes or cleaners on your lamp.
USE DRY CLOTH TO CLEAN.