



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-1336 - 50/45/40/35/30 Watt LED Light Bar Retrofit Kit;
3K/35K/4K/5K/65K CCT Selectable; 3-Bars; 4 Feet; 120-277 Volt; Silver Finish

- Wattage Selectable
- Flicker Free
- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	50W/45W/40W/35W/30W
Volts:	120V-277V
Lumens:	6250L/5625L/5000L/4375L/3750L
Lamp Base :	Integrated - Integrated
CRI:	80+
CCT (Kelvins):	30K/35K/40K/50K/65K - Soft White to Daylight
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 0-10V Dimming
Operating Temperature :	-4F to +113F (-20C to +45C)
Lamp Included :	Integrated
Replaceable Light Source :	No
Connection:	Hardwire
Surge Protection :	Built-in surge protection - 1KV
THD:	<20%
Power Factor :	>0.9
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923409882
Each Quantity:	1
Each Dimensions:	43.31 x 4.02 x 1.18

INFO

Additional Info:	Default CCT setting is 4000K; Default Wattage setting is 50W.
Specification Note:	Default CCT setting is 4000K; Default Wattage setting is 50W.
Includes:	Magnetic Feet, Screws, Wire nuts

PHYSICAL

Finish:	Silver
Lens Finish:	Frosted
Lens Material:	Polycarbonate (PC)
Dimensions:	L:41.73" W:0.93" H:1.19"
Weight (Lbs.):	2.1
Material:	Aluminum
Panel Size:	3x4

COMPLIANCE

Safety Listing:	cULus - Certified
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-8443ST
CA Prop 65:	Lead
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
Closet Rated:	No
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES



86-202R Add-On Microwave Sensor for High Bay Fixtures; 120-277 Volt



86-211 Add On PIR Sensor; White Finish; 120-277 Volt



86-214 Programming Remote for 86-202R



86-224 10KV Surge Protector; 100-277 Volt
