

Specifications

Style: Modern

Shape: Rectangular

Color: Gold

Material: PC, Tempered Glass, Stainless Steel

Surface Treatment: Polishing

Water Inlet: Lower Inlet

Mount Type: Wall Mounted

Installation Required: Yes

Support Thermostat: Yes

Screen Type: LED

Control Mode: Touch Control

Water Heater Lift: Unlimited

Heating Time: 3 Seconds Instant Heat

Waterproof Level: IPX4

Rated Voltage: AC 110V, 60HZ

Rated Power: 4500W

Rated Current: 40.9A

Rated Water Pressure: 0.6Mpa

Applicable Pressure: 0.02-0.6 MPa

Water Flow: 4L/1.06 gal/ min

Water Flow to Activate: 1.2-1.5L/0.32-0.4 gal/min

Temperature: 30-55°C/ 86-131 °F

Automatic Power-off Protection Temperature: 55°C/ 131 °F

Air Switch: $\geq 40A$

Wire Diameter: $\geq 4mm/0.16$ in

Magnetic Card Table: 10 (40) A

Mechanical Watch: $\geq 5(20)A$

Wire Requirements ≥ 4 Square Copper Core Wire

Hot Water Outlet Pipe Connector Diameter: 0.7cm/ 0.3in (Inner Diameter); 2cm/ 0.8in (Outer Diameter)

Cold Water Inlet Pipe Connector Diameter: 1.2cm/ 0.5in (Inner Diameter); 2cm/ 0.8in (Outer Diameter)

Gross Weight: 2.2kg/ 4.85 lbs

Net Weight: 2kg/ 4.41 lbs

Product Size: 27.7*18.6*5.7cm/10.9*7.32*2.24 in

Package Size: 32*27*12.5cm/ 12.6*10.63*4.92 in