

SPECIFICATION SHEET

BPL - 301


Fixture Specifications:

- Housing:** Die-cast aluminum.
- Stem:** Die-cast aluminum stem, with ½ NPT hub on bottom.
- Finish:** Polyester UV powder coated, available in **BLK-Black, RST-Rust**
- Socket:** G4 Bi-Pin socket
- Lamp:** 12V, JC Bi-Pin bulb 20W standard, 20W Max LED lamps available in 3W, with 2700K-warm white color temperature.

• Area Lights

• Aluminum

- Wiring:** Fixture is prewired with a 3ft 18-2 direct burial cord. Wire nuts sold separately.
- Mounting Spike:** Black 8½" ABS spike with ½" NPT male hub on top
- Electrical Notes:** A 12V transformer is required. Voltage range for 12V halogen lamps are 11V-12.5V. Voltage range for LED lamps are 8V-21V. Proper grease/lubricant is suggested on threaded parts during installation process.
- Warranty:** Limited five (5) year warranty on fixture housing and stem against manufacture's defects.



AVAILABLE LED LAMPS

LAMP NUMBER	BEAM		LUMEN	COLOR & TEMP.	RATED HOURS	HALOGEN EQUIVALENT
	WATTS	SPREAD				
LED3WG412V	3	360°	270	2700K	30000	20 Watt

AVAILABLE HALOGEN LAMPS

LAMP NUMBER	WATTS	BEAM		COLOR & TEMP.	RATED HOURS
		SPREAD	LUMEN		
JC10W	10	360°	75	2700K	2000
JC20W	20	360°	190	2700K	2000
JC35W	35	360°	265	2700K	2000
JC50W	50	360°	400	2700K	2000

