

XLED curved

Attractive buildings need attractive floodlights.

- LED floodlight with infrared sensor
- 20% more output
- 828 Lumen bei nur 10.5W
- 160° infrared motion detector
- Colour matched lens
- 50,000h LED lifetime (30 years at approx. 4.5 h/day)
- In white and anthracite colour
- 3 years warranty



XLED curved

Attractive buildings need attractive floodlights.

Technical data

Dimensions (HxWxD):	120 x 160 x 107 mm
Voltage:	230-240V, 50/60Hz
Output:	10.5 W
Luminous flux/efficiency:	828 lm, 78.9 lm/W
Colour temperature:	4000K neutralwhite, SDCM 4
LED lifetime:	50,000 h (L70B10)
Sensor technology:	Passive infrared
Angle of detection:	160°
Detection range:	8m max.
Response light level:	2 - 1000 Lux
Time setting:	2s – 70 Min.
IP-/protection class:	IP 44/ I
Own power consumption:	0.15W
Material:	Aluminium, UV-resistant plastic
Packing dimensions:	225 x 121 x 222 mm
Customs tariff number:	94051021
Country of origin:	Germany (start of production), Romania (serial production)
Region of origin:	14 (start of production), 03 (serial production)



EAN-Code	Art.-No.	Bezeichnung Description	VE min.order quan.
4007841 012083	012083	LED Strahler XLED curved white	1
4007841 012076	012076	LED Strahler XLED curved anthracite	1