



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-555 - 20/40/60 Watt LED Cutoff Wall Pack; 3K/4K/5K CCT; Field Selectable; Bronze; 120-347 Volt

- Wattage Selectable
- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	20W/40W/60W
Volts:	120V-347V
Lumens:	3056L-8421L
Lamp Base :	Integrated - Integrated
CRI:	80+
Rg Value :	5
CCT (Kelvins):	30K/40K/50K - Soft White to Natural Light
Beam Spread :	108
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 0-10V Dimming
HID Equivalent :	250W
Operating Temperature :	-40C (-40F) to +50C (+122F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Connection:	Hardwire
Surge Protection :	Built-in surge protection - 6KV
THD:	<20%
Power Factor :	>0.9
Voltage Type:	AC Only; Range Voltage
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923434150
Each Quantity:	1
Each Dimensions:	13.27 x 12.64 x 8.46

INFO

Specification Note:	Type II Light Distribution; For International Dark Sky Compliance the fixture CCT must be set to 3000K and installed in a downward facing and locked position
---------------------	---

PHYSICAL

Finish:	Bronze
Lens Finish:	Opaque
Lens Material:	Polycarbonate (PC)
Dimensions:	W:10.65" H:9.36" E:6.85"
Weight (Lbs.):	7.94
Material:	Die-Cast Aluminum
Sensor:	Yes - Bypassable

COMPLIANCE

Safety Listing:	cULus
Location Rating:	Wet
Indoor/Outdoor:	Outdoor
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-45Y2JF
CA Prop 65:	Lead
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK06
RoHS Compliant:	Yes
B.U.G Rating:	B2-U0-G2
Restrictions:	No Restrictions

ACCESSORIES



86-217 Add-On PIR Sensor; 6 Meter



86-218 Add-On Microwave Sensor; 12 Meter



86-219 Programming Remote Control for use with 86-218, 86-217 & 86-220 Sensors



86-220 Add-On PIR Sensor; 12 Meter

DIMMER COMPATIBILITY

Legrand ADPD4FBL3P2W4

Legrand CD4FBLW

Eaton DF10P

Leviton DS710-10Z

Lutron DVSCSTV

Lutron DVSTV

Leviton IP710-LFZ

Lutron MS-Z101

Lutron MS-Z101-V

Lutron NFTV

Lutron NTSTV-DV

Legrand RH4FBL3PTCCCV6

Lutron RMJS-8T-DV-B + PJ2-3BRL-GWH-Lo1
