

SCAN CODE FOR AN  
INSTALLATION VIDEO  
OF RETRO TILES!

### HOW MANY BOXES DO YOU NEED?

After measuring the room, use the chart below to determine  
how many 20-pack boxes you'll need to complete the job.

	0'	8"	10"	12"	14"	16"	18"	20"
6'	2	3	3	4	5	5	6	6
8'	3	4	4	5	6	7	8	8
10'	3	4	5	6	7	8	9	10
12'	4	5	6	8	9	10	11	12

### 3 YEAR LIMITED WARRANTY

The manufacturer warrants these Tiles to the original purchaser for a period of three years against manufacturing defects when installed according to instructions. The manufacturer will replace material of similar quality to the defective material. This warranty covers only new material purchased from an authorized dealer. Proof of purchase will be required. This warranty does not apply to damage from abrasion, heat, fire, wood stain, water accumulation, neglect, abuse, improper installation or maintenance, any usage other than residential interiors. The manufacturer's responsibility does not extend to any circumstances beyond the purchase price of the product.

### GANANTIA LIMITADA POR TRES AÑOS

El fabricante garantiza estos Tiles de este garantía al comprador original por un periodo de tres años contra de defectos de fabricación, cuando instalado de acuerdo con estas instrucciones del fabricante. El fabricante solamente reemplazara el material de la calidad similar al material defectuoso. Esta garantía cubre solo material nuevo cuando fue comprado de un comerciante autorizado. Prueba de la compra es requerido. Esta garantía no aplica a daños por desgaste de sucio, agua, fuego, manchas de madera, acumulación de agua, descuido, abuso, instalación incorrecta, mantenimiento apropiado, cualquier uso que no sea interior residencial.



Achim's Family of Home Furnishings  
Achim Importing Company, Inc.  
58 Second Ave, Brooklyn, NY 11215  
achimonline.com  
Made in China • 1/25.2M

RESIDENTIAL/LIGHT COMMERCIAL USE VINYL FLOOR TILES

SIMPLE PEEL'N STICK  
INSTALLATION  
PATTERN: SLATE

VINYL COMB

SELF-ADHESIVE PEEL'N STICK VINYL FLOOR TILES



# RETRO TILES

SELF-ADHESIVE PEEL'N STICK VINYL FLOOR



IDEAL FOR  
KITCHENS • BATHROOMS  
LAUNDRY ROOMS • FOYERS

SIMPLE PEEL'N STICK  
INSTALLATION

20 TILES PER BOX 12.12" TILE SIZE 31.48CM x 31.48CM 20 SQUARE FEET 1.86 SQ.M 15 MILLIMETER TILE GAUGE

TOOLS REQUIRED  
TAPE MEASURE, UTILITY KNIFE  
STRAIGHT EDGE



RETRO TILES SELF-ADHESIVE PEEL'N STICK VINYL FLOOR TILES

12.12" TILE SIZE 31.48CM x 31.48CM 20 SQUARE FEET 1.86 SQ.M 15 MILLIMETER TILE GAUGE 20 TILES PER BOX

RESIDENTIAL/LIGHT COMMERCIAL USE VINYL FLOOR TILES

SIMPLE PEEL'N STICK  
INSTALLATION  
PATTERN: SLATE

VINYL COMB

# RETRO TILES EASY DO-IT-YOURSELF INSTALLATION

TOOLS REQUIRED  
TAPE MEASURE, UTILITY KNIFE  
STRAIGHT EDGE

### INSTALLATION INSTRUCTIONS:


**IMPORTANT!** Make sure the PATTERN NAME located on the side of this box is the same when using two or more boxes. Before installing the Tiles, store them at room temperature for at least 4 day.

- PREPARING THE SURFACE**  
All floor surfaces MUST be dry, clean, smooth and level.
  - Concrete: Fill in all cracks and holes with a suitable latex filler and coat all areas with a suitable latex sealer that can be installed on unsealed concrete.
  - Wood: Make sure all planks or plywood are securely nailed down. Countersink nail heads, and cover with latex filler. The surface must be completely clean and free of paint, varnish, or wax and completely seal all areas with a suitable latex sealer.
  - Resilient Vinyl: Remove all dirt, grease, or wax build up.

DO NOT install tile over cushioned vinyl rubber flooring. Remove flooring or cover with plywood! If installing plywood, remember to counteract the nails and cover the holes with filler and then completely seal with a suitable latex sealer.

- DO NOT INSTALL TILES OVER:**
- Any floor exposed to excessive hot or cold temperatures.
  - Any floor exposed to excessive moisture.
  - Radiant heated floors.
  - Particle board or MDF Board.

**2. TO BEGIN:**  
You must determine the center point of your room. Measure the center points of opposite walls and secure a chalk line from one to the other. Stop the line. Repeat the process with the other set of opposite walls. The point at which the chalk lines intersect is the exact center.



**3. TILE INSTALLATION:**  
Starting at the center point as shown in Figure 1, peel off the protective paper and carefully align the tile with the chalk line markings. Press down firmly. Caution: the thin, protective paper covering is very slippery. In avoid accidents, do not leave the paper on the floor after you've started it from one side. Rotate each tile to the pattern match. Use this first tile as a slight variation in design match from tile to tile. This variation will not affect the overall look of your floor. Do your best to rotate tiles to the best look. Moving along the chalk line, put each tile squarely and as tightly as possible. Without going directly against the wall, install, from an "L" shape as shown in Figure 2. Cover a quarter of the surface area at a time. Do not install tiles to the edges of the room until the main floor area has been covered.

**4. CUTTING TILES:**  
Tiles should be cut with a straight edge and utility knife. Do not cut over newly installed tiles as the blade may damage the new tiles! Cut edges should face the wall. If possible, slide cut edge under wall molding. To fit tiles around irregularly shaped objects, make a pattern of the irregular area with a sheet of paper. Use the paper cut out as a template. Place the paper cut out on the front side of the tile, trace the contours of the paper onto the tile. Cut around the marked contours.

- 5. MAINTENANCE:**  
While Retro Tiles require minimum maintenance, please follow these guidelines:
- Sweep, damp mop, or vacuum regularly.
  - Avoid abrasive cleaners.
  - Use furniture leg covers.
  - Occasionally use an appropriate vinyl tile cleaner.
  - DO NOT WAX. This will make the floor's surface too slippery and may cause accidents.

# RETRO TILES

## EASY DO-IT-YOURSELF INSTALLATION

### TOOLS REQUIRED

TAPE MEASURE, UTILITY KNIFE  
STRAIGHT EDGE

### INSTALLATION INSTRUCTIONS:

**IMPORTANT:** Make sure the **PATTERN NAME** located on the side of this box is the same when using two or more boxes. Before installing the tiles, store them at room temperature for at least a day.

#### 1. PREPARING THE SURFACE

ALL floor surfaces MUST be dry, clean, smooth and level.

- **Cement:** Fill in all cracks and holes with a suitable latex filler and coat all areas with a suitable latex sealer. Not to be installed on untreated cement.
- **Wood:** Make sure all planks or plywoods are securely nailed down. Counter-sink nail heads, and cover with latex filler. The surface must be completely clean and free of paint, varnish, or wax and completely seal all areas with a suitable latex sealer.
- **Resilient Vinyl:** Remove all dirt, grease, or wax build up.

Do NOT install tiles over cushioned vinyl rubber flooring. Remove flooring or cover with plywood. If installing plywood, remember to countersink the nails and cover the holes with filler and then completely seal with a suitable latex sealer.

#### DO NOT INSTALL TILES OVER:

- Any floor exposed to excessively hot or cold temperatures.
- Any floor exposed to excessive moisture.
- Radiant heated floors.
- Particle board or MDF Board.

#### 2. TO BEGIN:

You must determine the center point of your room. Measure the center points of opposite walls and secure a chalk line from one to the other. Snap the line. Repeat the process with the other set of opposite walls. The point at which the chalk lines intersect is the room's center.




Figure 1

#### 3. TILE INSTALLATION:

Starting at the center point as shown in **Figure 1**, peel off the protective paper and carefully align the tile with the chalk line markings. Press down firmly. (Caution: the tile's protective paper covering is very slippery. To avoid accidents, do not leave the paper on the floor after you've peeled it from the tile.) Rotate next tile to find pattern match. You may find a slight variation in design match from tile to tile. This variation will not affect the overall look of your floor. Be sure to rotate tiles for best look. Moving along the chalk line, put each tile squarely and as tightly as possible. Without going directly against the wall initially, form an "L" shape as shown in **Figure 2**. Cover a quarter of the surface area at a time. Do not install tiles to the edges of the room until the main floor area has been covered.




Figure 2

#### 4. CUTTING TILES:

Tiles should be cut with a straight edge and utility knife. (Do not cut over newly installed tiles as the blade may damage the new tiles.) Cut edges should face the wall. If possible, slide cut edges under wall molding. To fit tiles around irregularly shaped objects, make a pattern of the exposed area with a sheet of paper. Use the paper cut-out as a template. Placing the paper cut-out on the front side of the tile, trace the contours of the paper onto the tile. Cut around the marked contours.

#### 5. MAINTENANCE:

While Retro Tiles require minimum maintenance, please follow these guidelines:

- Sweep, damp mop, or vacuum regularly.
- Avoid abrasive cleansers.
- Use furniture leg coasters.
- Occasionally use an appropriate vinyl tile cleaner.
- DO NOT WAX. This will make the floor's surface too slippery and may cause accidents.

## HOW MANY BOXES DO YOU NEED?

After measuring the room, use the chart below to determine how many 20-pack boxes you'll need to complete the job.

	6'	8'	10'	12'	14'	16'	18'	20'
6'	2	3	3	4	5	5	6	6
8'	3	4	4	5	6	7	8	8
10'	3	4	5	6	7	8	9	10
12'	4	5	6	8	9	10	11	12

## 3 YEAR LIMITED WARRANTY

The manufacturer warrants Retro Tile to the original purchaser for a period of three years against manufacturing defects, when installed according to instructions. The manufacturer will replace material of similar quality as the defective material. This warranty covers only new material purchased from an authorized dealer. Proof of purchase will be required. This warranty does not apply to damage from stiletto heels, tar, wood stain, water accumulation, neglect, abuse, improper installation or maintenance, any usage other than residential interiors. The manufacturer's compensation does not in any circumstance exceed the purchase price of the product.

### GARANTIA LIMITADA POR TRES AÑOS

El fabricante Retro Tiles da esta garantía al comprador original por un periodo de tres años contra de defectos de fabricación, cuando instalado de acuerdo con estas instrucciones del fabricante. El fabricante solamente reemplazara el material de la calidad similar al material defectuoso. Esta garantía cubre solo material Nuevo cuando fue comprado de un comerciante autorizado. Prueba de la compra es requerida. Esta garantía no aplica a danos por zapatos de tacon altos, brea, manchas de madera, acumulación de agua, descuido, abuso, instalacion incorrecta, mantenimiento inapropiado, cualquier uso que no sea interior residencial.