



Quinn Floor Lamp Assembly Instructions

1. Remove all parts and place on a flat surface
2. Screw pole B onto base A, then pole C to B, and pole D to C. Gently pull excess wire out through the hole in base A, making sure it doesn't get caught on the threading of the poles.
3. Connect assembled shade E onto socket using socket ring F. Ring F may be already screwed on in place on the socket, so you need to unscrew it first. Please refer to the second page for shade assembly instructions.

Extend Your Warranty From 3 Years To 5 Years

To extend your warranty by 2 extra years for a total of 5 years' warranty, register your purchase by filling in the brief form at <https://brightech.com/pages/extended-warranty> .

IMPORTANT SAFETY INSTRUCTIONS:

This portable lamp has a polarized plug (one blade is wider than the other) as a feature to reduce the risk of electric shock. This plug will fit in a polarized outlet only one way. If it does not fit fully in the outlet, reverse the plug. If it still does not fit, contact a qualified electrician. Never use with an extension cord unless the plug can be fully inserted. DO NOT ALTER THE PLUG

Max Wattage: 150 watt incandescent or 42 watt CFL equivalent. A 9.5 watt LED bulb is included. (Incandescent/CFL not included).

Please contact us via our website if you need any help with your new lamp.

www.brightech.com

