



**ENERGY STAR® Certified**  
In all 50 States



**Exterior Doors**  
**Fiberglass Door**  
**MLM-M-4 Low E**

**ENERGY PERFORMANCE RATINGS**

Product Description* Default Frame** Wood	U-Factor <sup>1</sup> /Solar Heat Gain Coefficient (SHGC)			
	Individual Option Number			
	1/4 Lite ≤410†	1/2 Lite ≤900†	3/4 Lite ≤1100†	Full Lite >1100†
Dual/Low E/Air/.75	0.21 / 0.09	0.24 / 0.16	0.27 / 0.21	0.30 / 0.28
	09575-00001	09576-00001	09577-00001	09578-00001
Dual/Low E/Air/.75 With Grids	0.23 / 0.09	0.28 / 0.17	0.31 / 0.23	0.35 / 0.30
	09579-00001	09580-00001	09581-00001	09582-00001
Dual/Low E/Air/.50 SDL	- / -	- / -	0.26 / 0.16	0.29 / 0.22
	-	-	09725-00001	09726-00001
Dual/Low E/Air/.81 With Blinds	- / -	0.24 / 0.08	0.27 / 0.11	0.30 / 0.15
	-	09796-00001	09797-00001	09798-00001
Triple/Low E/Air/.50/.31 With Blinds/Grids	- / -	0.22 / 0.10	- / -	0.25 / 0.19
	-	09805-00001	-	09806-00001
<b>Flush</b> 07941-00001	<b>U-Factor<sup>1</sup></b>	<b>0.16</b>	<b>SHGC</b>	<b>0.01</b>
<b>Embossed</b> 07942-00001	<b>U-Factor<sup>1</sup></b>	<b>0.17</b>	<b>SHGC</b>	<b>0.01</b>
<b>Air Leakage - ≤0.30 cfm/ft<sup>2</sup></b>				

09575-00001

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC rating are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for other product performance information.  
 \* #glazing layers / spacer type / low-e emissivity (surface) / gap fill / gap width (na=not applicable)  
 \*\* per NFRC 100 † square inches †btu/hr ft<sup>2</sup>F  
 \*\*\* Numbers below the performance ratings are referenced in the NFRC Certified Products Directory (e.g., ABC-X-1-00001-00001 or 123-X-1-00001-00001)  
 www.nfrc.org