



2*E26 Max 40W Not included

Dual-Arm Wall Sconce Instruction

Safety Warning

Turn OFF power at the breaker panel and verify the supply wires in the junction box are not live before beginning.

Installation Steps

• Step 1: Mount the Plate

Fasten the round mounting plate to the wall-mounted junction box using the two #8-32 screws provided. Position the two threaded studs so they face outward and sit level.

• Step 2: Make Electrical Connections

1. Connect black (hot) fixture wire to the black supply wire, white (neutral) to white, and green/bare (ground) to green/bare or the green ground screw on the plate.
2. Twist wire connectors clockwise until snug, then tuck the splices neatly inside the junction box.

• Step 3: Attach the Fixture Body

Align the fixture's backplate slots with the threaded studs on the mounting plate. Push the fixture flush to the wall, then thread the knurled cap nuts onto the studs and hand-tighten until the backplate is secure.

• Step 4: Remove the Shade Retaining Collars

On each socket assembly, unscrew the knurled retaining collar and set it aside. This opens the socket throat for bulb and shade installation.

• Step 5: Install the Bulbs

Screw two E26 medium-base bulbs (max 40 W each, not included) straight into the sockets. Do not exceed the wattage rating.

• Step 6: Position the Glass Shades

Carefully slide each glass shade over its socket, centering the neck of the shade against the socket plate. Support the shade with one hand.

• Step 7: Secure the Shades

Thread the knurled retaining collars removed in Step 4 back onto the sockets. Tighten by hand until each collar grips the shade firmly—snug but not overtightened.

Final Check

Restore power at the breaker panel and test the sconce. Both bulbs should illuminate evenly, and the shades should feel stable with no wobble.