



Project/Job Name: _____
 Location: _____
 Fixture Type: _____
 Notes: _____

S12460 - 5 Watt A19 LED; Clear; 2700K; Medium Base; 120 Volt; 4-Pack



ELECTRICAL

Technology:	LED
Watts:	5W
Volts:	120V
Lumens:	450L
CRI:	90
Rg Value :	52
CCT (Kelvins):	2700K - Warm White
Beam Spread :	280
Hours Rated:	15000
Dimmable:	Yes-Dimmable - 120V only
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable or Triac
Incandescent Equivalent :	40W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Power Factor :	0.7
Light Source:	LED Filament
Warranty:	3 Year Limited - 10 hr per day

PACKAGING

Each UPC:	045923124600
Each Quantity:	1
Each Dimensions:	10.24 x 2.56 x 4.72

PHYSICAL

Base:	Medium
Shape:	A19
Finish:	Clear
Dimensions (In.):	MOL: 2.36 - MOD: 2.36
Weight (Lbs.):	0.07
Material:	Glass
Housing Color:	Clear

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2405822
Energy Star Lamp Category:	Omnidirectional
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

DIMMER COMPATIBILITY

LEVITON 6672

LUTRON AYCL-153P

LUTRON AYCL-253P

LUTRON CTCL-153P

LUTRON CTRP-253P

LEVITON DDMX1

LEVITON DG6HD

LEVITON DH6HD

LEVITON DL6HD

LEVITON DSL06

LEVITON DSL06-1LZ

LUTRON DVCL-153P

LUTRON DVCL-253P

LUTRON DVRP-253P

LEVITON DZ6HD

LUTRON HQRA-PRO

LUTRON HQRD-10D

LUTRON HQRD-10NBD

LUTRON HQRD-6ND

LUTRON HQRD-HN6BRL

LUTRON HQRD-PRO

LUTRON HRST-PRO-N

LUTRON LECL-153P

LUTRON MA-PRO

LUTRON MACL-LFQ

LUTRON MRF2S-6ELV

LUTRON	NTCL-250
LUTRON	PD-10NXD
LUTRON	RCL-153PNL
LEVITON	RNL06-10Z
LUTRON	RRD-10D
LUTRON	RRD-6ND
LUTRON	RRD-H6BRL
LUTRON	RRD-PRO
LUTRON	RRST-PRO-N
SATCO	S11268
LUTRON	SCL-153P
LUTRON	ST-PRO-N
LUTRON	STCL-153M
Eaton	SUF7
LUTRON	TGCL-153PH
LEVITON	TSL06
LEVITON	TSM10
LUTRON	TTCL-100H