



Underscore® | K-1848-W1

60" x 36" drop-in bath with Bask® heated surface

Features

- Bask® heated surface creates spa-like relaxation with soothing warmth on your back, shoulders, and neck
- Customize the heat with three adjustable settings
- Integral lumbar support
- Slotted overflow allows for deep soaking



Available Colors/Finishes

Color tiles intended for reference only.

0	White
96	Biscuit
95	Ice Grey
7	Black Black



1-800-4KOHLER (1-800-456-4537)
Kohler Co. reserves the right to make revisions without notice to product specifications.
For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.
7-29-2026 20:34 - US-CA

THE BOLD LOOK
OF **KOHLER**

Codes/Standards

ASME A112.19.7/CSA B45.10
CSA B45.5/IAPMO Z124
ASTM E162
UL 1795
UL Listed

Technical Information

All product dimensions are nominal.

Drain Location:	Reversible
Drain Hole Diameter:	2-1/4" (57 mm)
Minimum Flat for Door:	2-1/2" (64 mm)
Basin Area, Bottom:	39-9/16" x 24-11/16" (1005 mm x 627 mm)
Basin Area, Top:	53-5/8" x 29-1/2" (1362 mm x 749 mm)
Water Depth:	17-1/8" (435 mm)
Water Capacity:	81.1 gal (307 L)
Minimum Floor Load:	52 lbs/ft ²
Weight:	81 lbs (36.7 kg)
Cutout:	Drop-in, 59-1/2" x 35-1/2" (1511 mm x 902 mm)

Material

- Acrylic

Required Products/Accessories

- K-7271 Slotted overflow brass bath drain
- or
- K-7272 Slotted overflow bath drain

Required Electrical Service

One circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

Heated surface: 120 V, 15 A, 60 Hz

Electrical Component Ratings

Heated surface: 120 V, 0.5 A, 60 Hz, 65 W

Warranty


See website for detailed warranty information.

KOHLER® Plastic Baths and Shower Bases Lifetime Limited Warranty|KOHLER® Hydrotherapy Components Five-Year Limited Warranty

Recommended Products/Accessories

K-1491 Bath/whirlpool pillow, removable
K-1601 Bath/whirlpool footstop, removable
K-1177 Tiling-in bead, 144" length
K-534 Undermount kit for select 60" Underscore bath models
K-23726 Drain treatment
K-23732 Tub & shower cleaner





Installation

- Reversible drain
- Drop-in or undermount
- Requires 110 V electrical service
- Under-mount installation requires kit K-534 (sold separately)
- Requires Clearflo slotted overflow bath drain (sold separately)

Installation Notes

Install this product according to the installation instructions.

Measure your actual product for rough-in details. The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary. Kit is required for under-mount installations (sold separately).

