

### To Use 3 way Water Diverter

To change water flow, turn Diverter Switch 90° with Knob pointing in the shutoff direction. Point Knob STRAIGHT to use Hand Shower, DOWN to use Shower Head or UP to use combination of both.

### To Adjust Angle of Hand Shower

Rotate Holder in vertical directions to set desired Hand Shower angle.

### To Adjust Angle of Shower Head

Slightly loosen swivel nut on back side of Shower Head and rotate Shower Head to desired angle within its movement range. Tighten swivel nut to lock position.

### To Use 5-function Shower Head and Hand Shower Dial

Turn Dial Lever to select desired water pattern for each shower. Choose from 5 full settings. When turning Shower Head dial, we recommend that you hold Shower Head with free hand to prevent accidental loosening of Diverter connection.

### To Save Water while Lathering or Shampooing

To stop water, turn Dial Lever to Economy Rain or PAUSE mode. For your safety (to prevent pressure buildup), PAUSE mode has water dripping instead of complete shut-off (Fig. 6). After use, DO NOT leave Dial set to Pause mode.


## Tips For Best Performance

As with all combination showers, using both showers together always causes water pressure to drop in each showerhead. Use shower head or hand shower individually to maximize water pressure for high-power performance. Use combined dual-shower application for gentle pampering, wider flow coverage and targeting of different body areas.

NOTE: This combination shower system is equipped with water flow regulator that limits maximum water flow to 2.5 gallons (9.5 liters) per minute at 80 psi water pressure when both showerheads work together or independently.

## Cleaning Instructions

To maintain proper working condition, clean flexible nozzles by rubbing with finger or soft bristled toothbrush, or soak in 50% white vinegar/50% water solution. If, over time, a loss of water pressure occurs due to build-up of residue and mineral deposits inside water flow regulator, you can remove Flow Regulator (Fig. 7) and soak it in white vinegar for 1/2 hour. DO NOT use harsh chemicals, heavy-duty cleaners or abrasives. This may damage parts or finish and may void warranty.



*If you have installation problem, please DO NOT return this product before calling our Toll Free Help Hotline first.*

**1-888-869-4010**

Mon. - Fri. 9:00 AM - 4:00 PM Eastern Time

ITEMS  
1441,  
2441

## LIFETIME LIMITED WARRANTY

Interlink will repair or replace any of this product's parts that exhibit defects in workmanship or materials for above stated period from date of purchase. If malfunction occurs, send only defective part(s) with proof of purchase to Customer Service Department at the address listed below. Your warranty does not cover malfunction or damage due to accident, misuse, or failure to follow any written instructions accompanying this product.

[www.ipshowers.com](http://www.ipshowers.com)

Interlink Products 1315 E. Elizabeth Ave., Linden, NJ 07036

US Patent No. 7,373,954 B2 Made in China

A112.18.1 Maximum Flow 2.5 Gallons Per Minute 9.5 Liters Per Minute