

Instruction Manual

Planning Installation

Read all instructions before assembling and installation. Before starting installation of this vanity fixture or removal of a previous fixture, turn off the water supply. Open the faucet handles to relieve water pressure and ensure complete water shut-off. To avoid any damage, assemble this product on a soft, non-abrasive surface such as a carpet or cardboard. Inspect each part for defects that may have occurred during shipping. Report any damaged or missing items to the Customer Service Team immediately.

Installing

1. For shipping purposes, the handles (B) are pre-installed on the inside of the drawers. Un-install the handles (B).
2. Re-attach the handles (B) onto the front of the drawers using handle screws.
3. Screw the leg (D) to the bottom of the cabinet (C).
4. If the floor is uneven, you can adjust the legs which are adjustable, so that the cabinet door or drawer can be balance.
5. When deciding the mounting location, note the location of the water supply lines.
6. Vertical position is decided by the purchaser, with a recommended height range of 33-in to 36-in from floor to top of basin.
7. According to the sealant manufacturer's recommendations, apply sealant to the top edges of the cabinet and wall. Do not over apply.
8. Gently place the basin (A) onto the cabinet (C). Allow to dry for twenty-four hours for proper curing.

Care and Cleaning

1. TO clean the fixture, wipe with a soft, dry cloth.
2. Do not let any sharp objects scratch the vanity.
3. Do not let the fixture come in contact with high heat sources.
4. Do not expose the vanity to direct prolonged sunlight. It will cause discoloration.
5. Do not use any cleaners with chemicals, solvents, or harsh abrasives.

