



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11874R1 - 10 Watt LED Direct Wire Downlight; 4-Inch; CCT Selectable; Round; Remote Driver; Black Finish

- Air Tight
- Has Driver
- CCT Selectable
- IC Rated



ELECTRICAL

Technology:	LED
Watts:	10W
Volts:	120V
Lumens:	850L
CRI:	90+
CCT (Kelvins):	27K/30K/35K/40K/50K - Warm White to Natural Light
Beam Spread :	110
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 120V Only
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Line Voltage
Incandescent Equivalent :	65W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Replaceable Light Source :	No
Connection:	Hardwire
THD:	<20%
Power Factor :	>0.9
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923411083
Each Quantity:	1
Each Dimensions:	4.92 x 2.36 x 5.39

INFO

Specification Note:	Suitable for use in clothes closets when installed in accordance with the NEC 410.16 spacing requirements
---------------------	---

PHYSICAL

Finish:	Black
Lens Finish:	Frost
Lens Material:	Poly methyl methacrylate (PMMA)
Dimensions:	H:0.99" DIA:4.75"
Weight (Lbs.):	0.86
Material:	Aluminum













INSTALLATION

Sloped Ceiling Compatible:	Yes
----------------------------	-----

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor and Outdoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-4480266
Energy Star Lamp Category:	Downlight Recessed
CA Prop 65:	Lead
BAA Compliant:	No
Closet Rated:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES

	80-865	4-Inch Asymmetric New Construction Recessed Downlight Mounting Plate; Flat
	80-867	Universal New Construction Recessed Downlight Mounting Plate; Flat; 3,5-Inch; 4-Inch; 6-Inch; 8-Inch
	80-943	New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/ Joist mounting of 4-inch Recessed Downlights; Up to 4.25-inch hole diameter
	80-946	4" Goof Ring for Remote Driver Installation
	80-949	6 FOOT REMOTE DRIVER 1-PIN EXT
	80-950	New Construction Mounting Plate for Stud/ Joist mounting of 4-inch Recessed Downlights; Up to 4.563-inch hole diameter
	80-973	Emergency Driver Enclosure; For use with S8000 and S8002
	80-987	Emergency Remote Test Switch; Single Gang Plate; White Finish
	80-997	Downlight Hanger Bar Kit; For Asymmetrical Plates; New Construction
	86-216	Temporary work light; LED; For use with remote drivers; Low voltage 10W/12W/24W; 3000K; 12 Volts
	S8000	5 Watt LED Emergency Driver; 120-277 Volts
	S8002	10 Watt LED Emergency Driver; 120-277 Volt