

Project:

Thin-Line Indirect LED Wall Bar Spec Sheet

SKU: 2814.03-8 Learn more at:
<https://sonnemanlight.com/thin-line-indirect-led-wall-bar>

Description:

A system of minimally scaled LED indirect light wall bars, uplight/downlight wall bars, and pendants. Thin-Line is offered in a variety of lengths, finishes, and lighting configurations. Indirect configurations reflect light back onto the wall or mounting surface to radiate indirect illumination.



Type #:



Dimensions

Height:	0.75"
Width:	96"
Extends:	3.5"
Minimum Extension:	3.5"
Maximum Extension:	3.5"
Size:	8'
Canopy/Backplate/Base Width:	1
Canopy/Backplate/Base Height:	0.75

Electrical Specs

Bulb(s) Included?:	Yes
Bulb 1 Type:	Integral LED
Bulb Quantity:	1
Input Voltage:	120VAC
Wattage:	47
Initial Lumens:	3120
Delivered Lumens:	1800
Color Temperature:	3000K
CRI:	90
Power Supply Type:	Driver
Power Supply Quantity:	1
Power Supply Location:	Remote
Dimming Type:	TRIAC/ELV
Bulb Max Wattage:	47

Installation

Installation:	Licensed electrician required
Installation Orientation:	Any Orientation

Shipping

Carton 1 L x W x H:	99" X 7" X 4"
Carton 1 Gross Weight:	8 LBS

Shade

Shade 1 Material:	Aluminum w/Optical Acrylic
-------------------	----------------------------

Available Finishes

Available Finishes: Bright Satin Aluminum (.16), Satin Black (.25), Satin White (.03)

General Listings

Features:	Damp Rated, On Sale
Certification:	C-ETL-US
Color/Finish:	Satin White (.03)
Dark Sky Friendly:	N