


MT-5LD225 - 2 Lights

Tesla LED Multiple Spots Energy Star®

WAC LIGHTING
Responsible Lighting®



PRODUCT DESCRIPTION

High brightness, individually retractable & adjustable spot lights.

FEATURES

- Energy Star® rated
- Non-IC rated, airtight housings
- Invisible Trim™ is designed to sit flush with the ceiling for a clean, architectural look
- Spot and Flood beam spreads
- 45° vertical adjustment and 365° horizontal rotation
- Accepts one replacement lens
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

FIXTURE PERFORMANCE

Model #	Beam	CCT	Watts	Lumens	Efficacy	CRI
MT-5LD225T-S927	25°	2700K	22.5W	1992	44 Lm/W	90
MT-5LD225T-F927	40°			2041	45 Lm/W	
MT-5LD225T-S27	25°	2700K	22.5W	2490	55 Lm/W	85
MT-5LD225T-F27	40°			2490	55 Lm/W	
MT-5LD225T-S930	25°	3000K	22.5W	2224	49 Lm/W	90
MT-5LD225T-F930	45°			2136	48 Lm/W	
MT-5LD225T-S30	25°	3000K	22.5W	2780	62 Lm/W	85
MT-5LD225T-F30	45°			2670	59 Lm/W	
MT-5LD225T-S35	25°	3500K	22.5W	2700	60 Lm/W	85
MT-5LD225T-F35	40°			2660	59 Lm/W	
MT-5LD225T-S40	25°	4000K	22.5W	3030	67 Lm/W	85
MT-5LD225T-F40	40°			2900	64 Lm/W	

TRIM ORDER NUMBER

Model #	Beam	Color Temp	Rated	Finish
MT-5LD225T	Trim	927 2700K (90 CRI) 27 2700K 930 3000K (90 CRI) 30 3000K 35 3500K 40 4000K	Non-IC	WT White
MT-5LD225TL	Invisible Trim™			

Example: MT-5LD225T-S30-WT

Fixture Type:

Catalog Number:

Project:

Location:

SPECIFICATIONS

Construction: Die-cast aluminum heat sink painted white. Trim, housing and junction box are 20 gauge steel. Frame and hanger bars are heavy gauge galvanized steel.

J-Box: Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: Universal Input (120V - 277V)

Light Source: High output LED (included with housing)

Dimming: Dim to 10% with electronic low voltage (ELV) dimmer.

Mounting: Supplied with hanger bars, adjustable from 15"-24½" to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surface up to 1" thick. 11 13/16" x 6 1/8" cutout with trim, 13 3/8" x 7 3/4" cutout for Invisible Trim™. See instruction sheet for details on installation using spackle ring.

Finish: Abrasion resistant powder coat paint in White (WT).

Standards: ETL & cETL listed.

COLOR LENSES LENSES

Color Lens	LENS-16	LENS-16-DIC
Dichroic Color Lens		
	AMB Amber	
	BLU Blue	
	GRN Green	
	RED Red	
	YEL Yellow	

LENSES

Clear Lens	LENS-16-CL
Frosted Lens	LENS-16-FR
Spread Lens	LENS-16-SPR
Beam Soft Lens	LENS-16-BSL
Beam Elongating Lens	LENS-16-BEL
Infrared Filter Lens	LENS-16-IR
UV/Infrared Filter Lens	LENS-16-UI


ACCESSORIES

Honeycomb Louver	LENS-16-HCL
Cross Louver	LENS-16-CRL
2" Snoot	LENS-16-SNOOT

HOUSING ORDER NUMBER

Non-IC Rated, Airtight New Construction

MT-5LD225H-NA



WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive • Port Washington, NY 11050
Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center
1750 Archibald Avenue • Ontario, CA 91760
Phone (800) 526.2588 • Fax (800) 526.2585