#### location: DAMP interior

# interior







## **SPECIFICATIONS:**

#### **DESCRIPTION**

Wall-mounted ADA-compliant sconce featuring open-ended handcrafted glass.

#### **LAMPING**

**Standard:** 2x 75W A19 120V incandescent, suitable for dimming. **CFL:** 18W 4-Pin CFL with non-dimming electronic ballast. 120V, *lamp not included.* 

**T5 CFL:** 24W Twin T5 CFL with non-dimming electronic ballast. **GU24 CFL:** Self-ballasted GU24 lampholders. 18W max, 120V, *lamp not included.* 

LED: 10W GU24 LED Lamp 120V, dimmable, included.

#### **DIFFUSER**

Diffuser shall be handcrafted glass of various decors.

### **CONSTRUCTION**

Glass is secured to the backplate by decorative thumbscrews. Rectangular backplate (nominal 4"W x 17.25" H) shall be constructed of steel, powder-coated white.

#### **METAL FINISH**

Decorative metal accents shall be in various finish options.

#### **MOUNTING**

Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. Top of glass is approximately 3.625" above the outlet box centerline.

#### **LABELS**

UL or ETL Listed. Suitable for Damp Locations (interior use only).






### For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

sconces

## **ORDERING:**

8 1 9 3			
Torre 18 Fixture/Decor	Lamp Options	Metal Finish	
819307 White 8193CF Copper Foil 8193CH Cherry 8193GF Gold Foil 8193KR Chalk	(blank) 2x 75W A19 Incan E2 2x 18W Quad 120V N2 2x 18W Quad 277V 124T5 1x 24W Twin T5 120/277V GU24 2x 18W GU24 120V	BK Black BR Bronze PN Polished Nickel SN Satin Nickel WH White	
81930K Oak 8193SF Silver Foil 8193TN Titan	LED 2x 6W LED 120V, non-dimmable		



## **LED WALL SCONCES:**

- Internal driver integrated in the lamp, GU24 base
- Total power of only 10 watts
- Dimmable with a standard dimmer
- Rated life: 30,000 hours
- Frosted acrylic diffuser
- 820 lumens
- CCT: 2700° Kelvin
- CRI: 82
- 3 year warranty

Project Information:		