

SUPERIORE



Range with a contemporary design and an unparalleled level of cooking flexibility thanks to its 6 burners and griddle configuration. That is the ideal worktop for its 2 gas ovens with the main cavity equipped with 2 convection fans and broiler.

Featured Product



Color	Style	Decò accents	Fuel
Stainless steel	NEXT Line	Steel	Mixed Gas/Electric
Installation	Version	Levels	Width
Free Standing	Duct-out	1	48"
Depth			
24"			

WORKTOP

Design	Gas burners	Gas brass burners	↳ Power burner with simmer (n° 1)
Squared worktop with bull nose	6	6	750--18,000 Btu/h (min -- max)
↳ Power burner (n° 1)	↳ Large burner (n° 1)	↳ Medium burner (n° 2)	↳ Auxiliary (n° 1)
4,750--18,000 Btu/h (min -- max)	2,750--11,000 Btu/h (min -- max)	2,050--6,500 Btu/h (min -- max)	1,100--3,600 Btu/h (min -- max)
Total gas power	Grates	Ignition	Gas safety
63,600 Btu/h	Cast Iron	One Hand	Thermocouples
Wok ring	Simmer ring	Interface	Electric griddle Type
Standard	Standard	Knob	Stainless Steel
Electric griddle Power	Removable drip tray	Backguard	Island trim
1,150 W	Standard	Optional	Standard

OVEN CAVITY

Oven(s)	Main oven type	Auxiliary oven type	Main oven functions
2	Gas Oven with Gas Grill	Gas	
Auxiliary oven functions	Oven convection fans	Main overall cavity volume	Auxiliary overall cavity volume
	2	5.7 cu.ft	3.0 cu.ft
Main interior dimension (WxDxH)	Auxiliary interior dimension (WxDxH)	Enamel	Enamel color
24" ¹³ / ₁₆ x 19" ⁵⁷ / ₆₄ x 20" ³¹ / ₆₄	9" ¹⁷ / ₆₄ x 19" ⁵⁵ / ₆₄ x 20" ³¹ / ₆₄	Easy to Clean	Light Grey
Smooth oven interior	Oven control device	Maximum cooking temperature	Cooling fan
Standard	Analog Thermometer	500 °F	Standard
Door type	Door design	Glasses	Main oven lights
Fully Flush	Panorama	3	2
Auxiliary oven lights			
2			

EQUIPMENT

telescopic glide shelves	Main Oven wire shelves	Auxiliary Oven wire shelves	enamelled trays
1 set	2	1	1
trivet			
1			

BELOW

Feet	Stainless steel toekick
Stainless Steel Adjustable	Optional

CONNECTIONS AND WARRANTY

Gas adjustment: natural gas	Gas adjustment: LPG	Voltage -- Frequency	Certification
Standard	Standard accessory- Model RN482GPS_SL	120 -- 60 V -- Hz	CSA, Star-K
Warranty			
2 years			