

3" Square Regressed Gimbal LED 7.5W



Type IC, Wet & Air-Tight

DESCRIPTION

3" Square Regressed Gimbal LED
With Integral Driver In Connection Box
Unique & Patented Design:
Gimbal Yet Air-Tight Without Housing Needed


FEATURES & BENEFITS

2 1/2" Deep - Install Where Ceiling Space Is Limited
Type IC Rated - No Housing Required
Fast & Easy To Install - Save On Labor
Driver Inside Connection Box - No Junction Box Needed
Directional Beam - Great for Sloped Ceilings and Artwork
CRI 90+ for True Color Rendering

MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening
With Attached Spring Clips
Ceiling Clearance Required:
2 1/2" for Romex | 3 1/2" for MC or BX installations

DIMENSIONS: ID 3 1/4" OD 4 1/4" Sq Cut Out 3 1/4" to 3 1/2"



120V TRIAC Dimmable Driver Included



Optional 120V-347V Driver 0-10V Dimmable



Order Separately as
Cat # LLL-LD0716T

ORDERING GUIDE Example: **LSG3 - 30K - WH**

	CCT	Trim Finish	Beam Angle
LSG3	-	-	-
2700K	27K	WH	for 38° leave blank
3000K	30K	BK	- 15D spot 15°
4000K	40K		
Dim to Warm 3000K to 2000K	32K	White Trim & 38° Only In Stock	

Project: _____

Location: _____

Cat #: _____ Qty: _____

Notes: _____

SPECIFICATION

Applications	Sloped Ceilings, Highlighting Artwork	
Energy Used	7.5 W	
Color Temperature	2700 3000 4000 DTW 30-20	
Light Output	580 600 630 500	
Halogen Equivalent	50 W	
Beam Angle	38° or 15° with 20° tilt and 360° rotation	
CRI	90 +	
Default Driver Input	120V AC	Triac Dimmable
Optional Driver Input	120V-347V AC	0-10V Dimmable
Power Factor	0.95	
Approved Location	Insulated Ceiling & Wet Locations	
IP Rating	IP 54	
Air Tight	Yes	
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)	
Projected Life	70% Light Output at 50,000 Hours	
Certification	cULus, Energy Star (except DTW), T24	
Warranty	10 Year on Residential 5 Year on Commercial Applications	

AVAILABLE TRIMS



White



Black

ACCESSORIES

Sold Separately



Low Voltage Extension Cables
6ft - cat # **EXC6**, 20ft - cat # **EXC20**
Max 40 ft Allowed. FT4 / CMR rated



Flat Rough-In Plates - cat # **RIP312**



Flanged Rough-In Plate - cat # **FRP312**

COMPLIANCE



**Type IC
Air-Tight**

USA Patent # US 10,344,952 B2 | Canada Patent # 2,967,954