

3.5" OCULUX - 0-35° Adjustable

R3BRA, R3BSA

WAC LIGHTING
Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Designed to fit in tight plenum space

FEATURES

- Energy Star® Rated
- Title 24 Compliant
- IC-rated Remodel and New Construction
- Airtight in New Construction and remodel
- Shallow housing under 4" depth
- Cutout 4¼"
- Single spot light source

SPECIFICATIONS

Construction: Die-cast aluminum trim and heat sink

Dimming: ELV or TRIAC or 0-10V dimming compatible

Input: 120V for R3BNICA-10, R3BBRT-10; 120-277V for R3BNICA-10U

Power: 11W

Mounting: Retention clips firmly hold trim to housing.

Finish: Powder coated

Ceiling thickness: ½" - 1"

Standards: ETL&cETL listed, Damp location listed

Operating Temperature: -4°F to 104°F (20°C to 40°C)

Trims (Order Housing Separately)	Model	Beam	Color Temp	Max Lumens	Max CBCP	Finish
	R3BRA Round 0 - 35° Adjustable 48° visual cutoff	S 15°	927 2700K	900	4384	HZWT Haze/White BN Brushed Nickel WT White
			930 3000K	970	4712	
		N 25°	927 2700K	915	2513	
			930 3000K	985	2701	
		F 50°	927 2700K	900	1196	
			930 3000K	970	1285	
	R3BSA Square 0 - 35° Adjustable 48° visual cutoff	S 15°	927 2700K	900	4384	HZWT Haze/White BN Brushed Nickel WT White
			930 3000K	970	4712	
		N 25°	927 2700K	915	2513	
			930 3000K	985	2701	
		F 50°	927 2700K	900	1196	
			930 3000K	970	1285	

R3BRA- - -

Example: R3BRA-S930-WT

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760






3.5" OCULUX - 0-35° Adjustable

R3BRA, R3BSA

WAC LIGHTING

Responsible Lighting®

Housings (Required) - Order separately from trims

		Model	Input	Dimming	Notes
New Construction  14½" min 24½" max		R3BNICA-10 IC-Rated, Airtight	120V	100% - 5% TRIAC, ELV, 0-10V	Less than 4" plenum depth
		R3BNICA-10U IC-Rated, Airtight	120V - 277V	120V 100% - 5% TRIAC, ELV, 0-10V 277V 100% - 1% 0-10V	Allows adjustment in any direction when used with adjustable trims Ceiling thickness: ½" - 1"
New Construction 2 Hour Fire Rated  14½" min 24½" max		R3BNICAF-10 IC-Rated, Airtight, Fire Rated	120V	100% - 5% TRIAC, ELV, 0-10V	Double sheet metal housing Supports two layer fire rated drywall ANSI / UL 263 Fire Rated Allows adjustment in any direction when used with adjustable trims Ceiling thickness: ½" - 1"
Remodel  2 1/16"		R3BBRT-10 IC Rated	120V	100% - 5% TRIAC, ELV, 0-10V	Allows adjustment in any direction when used with adjustable trims Ceiling thickness: ½" - 1"

Example: **R3BNICAF-10**

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760