

INSTALLATION INSTRUCTION

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

PREPARING FOR INSTALLATION (Fig. 1)

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to misplace any small parts necessary for installation.
3. Thread finial (A) into all thread (B) on top of fixture.

CONNECTING THE WIRES (Fig. 2)

4. Pull the black, white and ground wires out of the post.
5. While carefully supporting the fixture, connect the electrical wires as shown in Fig. 2. If your post has a ground wire (green or bare copper), connect the fixture's ground wire to it. If not, consult your electrician for proper grounding. After wires are connected, tuck them carefully inside the post.

COMPLETING THE INSTALLATION (Fig. 1)

6. Slide fixture over post and secure with screws (K).
7. Pull up latch (E) and open the door. Attach crystal pentalogs (C) into the holes on reflector (D).
8. Place candle covers (I) over sockets (J).
9. Install (2) two candelabra base bulbs (F) up to 60 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification—**DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**.
10. When replacing front glass (G), pull up latch (E) and open the door. Lift tabs and remove the side glass (H) first and then front glass (G). Next replace front glass (H) and side glass (H). Push down tabs to secure glass. Relatch (E) the door.
11. For installing or replacing bulbs at a later date, pull up latch (E) and open the door. (Fig. 1).

Your installation is now complete. Return the power to the outlet box and test the fixture.

Note: Illustration (Fig. 1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

