





Please contact jumptastictrampolines@gmail.com for customer service and more products.

SW318



IMPORTANT - READ AND FOLLOW ALL SAFETY INFORMATION AND INSTRUCTIONS, KEEP FOR FUTURE REFERENCE




WARNING! MAXIUMWEIGHT SHOULD NOT EXCEED 100 KGS.
WARNING! DO NOT USE WITHOUT ADULT SUPERVISION!
WARNING! ADULT ASSEMBLING REQUIRED!
RECOMMEND FOR AGES 3 YEARS OLD AND UP.

Direction for use

Please keep this instruction sheet safely for future reference.

- I. Inappropriate use or faulty application of the product is explicitly forbidden and absolves the manufacturer of all liability. This product needs to be mounted and checked thoroughly by an adult before use.
- 2. The use of the item is allowed only under continuous supervision by an adult. The product is suitable for individuals weighing up to 100 kg.
- 3. This product is intended for family domestic and outdoor use only.
- 4. When installing the product, ensure that the play system or other construction can support the weight and that there is no risk of entrapment.
- 5. The product should be placed on a level surface at least 2 m distance to any structure or obstruction such as a fence, garage, house, overhanging branches, laundry lines or electrical wires; the safety zone (shock absorbing, soft surface) should be 2 m added to rope length at front and back.
- 6. In this safety area no hard, angular or spiky objects should be present. The surface underneath the product should be flat and shock absorbing. The product must not be placed on asphalt, concrete or any other hard surface. We advise the removal and storage of all accessories during the winter because the characteristics of the soil (when frozen) are not suitable for safe play.
- 7. Please do not exposure to the sun long-term if not in use.
- 8. Installation method: installation of the product on the horizontal bar happens by linking the metal ring with the connective strap and spring hook. See fig.l.
- 9. The distance between the suspension points along the crossbeam equals or is more than the distance between the junction points of the swing element, plus 4% of the distance between the ground and beam.
- 10. The minimum distance from the bottom of the product to the ground surface shall be not less than 35 cm and not more than 55 cm.
- II. The minimum distance between the play equipment as well as the distance between the play equipment and the frame should be 45cm.







Please contact jumptastictrampolines@gmail.com for customer service and more products.

- 12. Please ensure that the crossbeam is never higher than 2.5m. Please make sure that children do not climb the seat to reach the top beam.
- 13. All pieces should be checked regularly. For replacement material and expansion of the playground equipment, please contact the supplier to guarantee the safety.

Inspection and maintenance

The frequency of inspection and maintenance will vary with the type of equipment of materials used or other factors (e.g. heavy use, levels of vandalism, coastal location, air pollution, age of equipment). Special attention should be given to the swing hooks, rings, carabiner hooks, plastic welds and ropes. Moving metal parts must be oiled regularly.

Routine visual inspection (weekly to monthly)

- Always check that the connectors are securely fastened.
- Check the shock absorbing surface for objects that don't belong there.
- Check for missing parts.
- Check the equipment ground clearances.

Operational inspection (1 to 3 months)

- Check the stability of the construction.
- Check every part for excessive wear and remove when necessary.

Annual inspection (I up to 2 times per year)

- Check for rust and corrosion.
- Check every part for excessive wear and remove when necessary.



WARNING! Small parts for assembly by an adult.




Fig. I