



ASSEMBLY INSTRUCTION

***BEFORE YOU BEGIN . . .**

- (1) Inspect lamp before beginning assembly
All wire connections have been made at the factory and the lamp is ready for assembly.
- (2) In order to prevent bad connections avoid pulling wire connections when removing contents from the package or during the installation.

PREINSTALLED HARDWARE (FIND AT LOCATIONS)

- 1 FLAT WASHER (Location F)
- 2 NUT (Location F)
- 5 PLASTIC SCREWS (Location G)
- 1 SCREW (Location E)

***ASSEMBLY INSTRUCTION...**

- (1) Insert the threaded nipple of pole (A) into the base (B), then tighten securely with the provided nut (C).

IMPORTANT SWITCH AND LAMPSHADES MUST BE FACING THE U SHAPE IN SECTION "B"

- (2) Connect the wire of pole (A) with the wire of arch base (D)

- (3) Insert the arch base (D) into the pole (A). tighten securely.

- (4) Tighten screw to pole (A)

- (5) Place flower-like lampshades into holder and tighten them up with plastic nuts provided.

**CAUTION: TO REDUCE THE RISK OF FIRE,
USE 40 WATT TYPE A, 4 PCS., CFL COMPATIBLE,
120V 60 HZ ONLY.**