## **USER MANUAL**



# LP500V2

### Advanced Small Handheld LED Flashlight





#### Features

Constructed with aircraft-grade aluminum

LPE optics

Patented TackGrip rubber grip

High quality wrist lanyard

Tactical on/off button

IPX4 waterproof rating

Batteries included (3 AAA)

#### ANSI/PLATO FL1 STANDARD

MODES		<b>C</b> RUN TIME	BEAM DISTANCE
High	330 lm	3h	165m
Medium	120 lm	7h 30m	80m
Low	35 lm	15h 15m	20m
Strobe	330 lm		

#### **Operation Instructions**

**On/Off:** Press and release the button on the tail cap to turn the light on and off.



**Cycle Modes:** Press button on tail cap quickly to cycle through modes (High/Medium/Ultra-Low). If light remains in a single mode for longer than 3-5 seconds, the next press of the button will turn the light off.

Light automatically resets to High mode when turned off.

**Hidden Strobe On/Off:** Press and hold button for 3 seconds to activate hidden strobe. Flashlight will remain in hidden strobe mode until it is deactivated by pushing and holding the button for 3 seconds again.

#### **Battery Replacement**

The LP500V2 uses 3 AAA batteries.

To replace the batteries, turn the tail cap counterclockwise to remove it. Tip the light downward to slide out the battery case which contains the batteries. Remove the batteries from the case and install new batteries with the negative side of the battery against the springs in the battery case. For best results, we recommend using brand new alkaline batteries that are the same voltage and brand. Re-insert battery case with the arrow on the battery case pointing down. Re-attach the tail cap by pressing down lightly and turning it clockwise until tight.



If you know it will be a while between uses, we suggest removing the batteries from the flashlight and storing it in a dry, protected place.

#### **Product Warranty**

The LP500V2 has a Limited Lifetime Warranty Against Manufacturer's Defects from time of purchase.

For warranty claims please contact us by calling 801-553-8886 or sending an email to info@simpleproducts.com