



**Submitted Model No.:** 

#### **Specific Features:**



# ▲Designate Proper Finish Suffix





# TUB AND SHOWER **FAUCET TRIM**

- Zura<sup>™</sup> Bath Collection
- Valve Only (T17074 Series)
- Shower Only (T17274 Series)
- Tub/Shower (T17474 Series)

#### **FEATURES:**

- Monitor® 17 Series pressure balanced bath mixing valve trim
- Three-setting H<sub>2</sub>Okinetic® Technology showerhead

## **STANDARD SPECIFICATIONS:**

- Maintains a balanced pressure of hot and cold water even when a valve is turned on or off elsewhere in the system.
- Max. 2.0 gpm @ 80 psi, 7.60 L/min @ 550 kPa.
- For use with MultiChoice® Universal rough valve body. (R10000 Series)
- Back-to-back installation capability.
- Solid brass forged body.
- Lever volume control handle; temperature adjustment dial.
- Field adjustable to limit handle rotation into hot water zone.
- Maximum dial rotation adjustable between 90° and 180°.
- All parts replaceable from the front of the valve.
- Red/blue pad print temperature indicators on temperature adjustment dial.
- Stem extension kit RP77992 can be ordered to allow for an additional 1 3/4" wall thickness. RP77992 ships with chrome escutcheon screws. For special finishes also order RP12630 escutcheon screws in desired finish.

#### **WARRANTY**


- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.



### **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1
- ASSE 1016

☐ Indicates compliance to
☐ ICC/ANSI A117.1 - Valve control only.
■ EPA WaterSense®





55 E 111th Street, Indianapolis, Indiana 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2016 Masco Corporation of Indiana