

NO.2396 INSTALLATION INSTRUCTIONS



Please Scan the QR code to watch the installation video. If you have any questions, please feel free to contact us through the order page.

Warning

1. Installation should be performed by a professional.
2. To prevent electric shock, please turn off the power before installing, repairing, or cleaning the light fixture.
3. This light fixture operates within a 110V to 265V range only.
4. Do not install the light fixture in damp conditions.
5. Keep the light fixture away from acidic and corrosive materials.
6. The light fixture is not compatible with dimmer switches; please use a standard on/off wall switch or the included remote control.

Specific Steps:

1.



Step 1: Assemble the light fixture.

Use a screwdriver to secure the lamp body by aligning and locking the positioning holes.

2.



Step 2: Insert plugs into control block.

Carefully insert the two small plugs into the control block. Any port can be used.

3.



Step 3: Attach the mounting plate to the wall.

Use the expansion bolts and screws provided in the accessories kit.

4.



Step 4: Connect the wires of the light fixture to the wires on the wall.

Connect the black wire to the live wire (L)
Connect the white wire to the neutral wire (N)

5.



Step 5: Secure the back plate using screws and nuts.

It is recommended that two people work together for the installation to ensure efficiency and safety.

Notice

Using the wall switch, the flush mount can switch between warm light, neutral light and white light.

If you adjust to one color temperature and maintain it for more than 10 seconds, the next time you turn on the lamp, it will default to the color temperature you turned off.