

# OUTDOOR WALL BRACKET

These instructions are provided for your safety.  
Please read them carefully before commencing work and retain them for future reference.

## SAFETY INFORMATION




**This fitting has an IP rating of IP44 and is suitable for outdoor use when connected as below.**

- \* If you are in any doubt consult a person competent to give advice on the installation of electrical equipment.
- \* Before installation and servicing disconnect the electricity supply at the fuse board.
- \* To avoid damage to concealed wiring during installation, establish the direction of the supply cable before drilling fixing holes.
- \* This fitting should be fitted to a lighting supply protected by a 5 amp fuse or equivalent circuit breaker.
- \* Always be sure to use the correct type and wattage of bulbs as indicated on the fitting. Dispose of old bulbs carefully.

## INSTALLATION

**Note: This fitting has a 3 year guarantee against corrosion. This fitting should only be installed in normal non aggressive atmospheric locations to prevent corrosion. Aggressive environments to be avoided include locations by the sea, polluted atmospheres or near heating flue outlets.**

1. Ensure the house electricity supply is off at the fuse board.
2. If removing an existing fitting, first note down all wiring connections.
3. Unscrew nuts from front of backplate of wall bracket.  
Remove mounting bracket from fitting and fix firmly to the wall.
4. Unscrew four screws holding cover onto box.
5. Unclip connector block from inside box.
6. Push small screwdriver through soft grommet in back of box.



7. Feed supply cable from house supply through hole in soft grommet which will form a seal around the cable
  8. The weight of the fitting must be supported whilst you make the electrical connections.  
Make all electrical connections through the connector block.  
Ensure electrical connections are tight and no loose strands of wire are left out of the block.  
Connect the live (brown) wire of the wall light to the supply live wire.  
Connect the neutral (blue) wire of the wall light to the supply neutral wire.  
The fitting is double insulated and no earth is required.
  9. Ensure electrical connections are tight and no loose strands of wire are left out of the connector block.
  10. Replace cover on box.
  11. Fix fitting to wall by threading backplate onto screws in fixing bracket and holding in place with the nuts. Ensure the fitting is attached to the wall the correct way up with the bracket attached to the bottom of the fitting only.
  12. To fit bulb:  
Remove the top lid by unscrewing the top decorative finial.  
Fit the bulb in the fitting.  
Re-assembly is the reverse of the above ensuring the lid is seated correctly before the finial is screwed back into position.
- The wattage indicated must not be exceeded.**
13. Switch on the electricity supply at the fuse board.

### **GENERAL INFORMATION**

This fitting is designed for external use, it must be fitted to a DRY FINISH as any dampness in concrete, wood stain, paint and etc can damage finish. **Do not use polish or abrasive cleaner - just a soft slightly damp cloth.**