


HR-2LED-T509

2" Tesla™ LED Square 0-30° Adjustable

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Minimum profile, square 0° to 30° adjustable trim with interior open reflector.

FEATURES

- 2" aperture
- CEC Title 24 Compliant (see below for list of models)
- Damp location listed
- 30° visual cutoff angle for glare control
- Adjustable fixtures are ideal for sloped ceiling applications
- 90,000 hours rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

Light Source: Utilizes one 14.5W LED, CRI: 85 & 90+

Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)

Mounting: Two heavy gauge retention clips hold trim firmly to housing

Finish: White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

Standards: ETL & cETL Listed.

See table below for California Title 24 Compliant for qualifying products.

TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	2013 Title 24	Finish
HR-2LED-T509 0°- 30° Adjustable	S 15°	27 2700K	85	528	1991	No	BN Brushed Nickel CB Copper Bronze WT White
		W 3000K	85	624	2407	No	
		9W 3000K	90	562	2129	No	
		35 3500K	85	594	2240	No	
		C 4000K	85	612	2305	No	
	N 26°	27 2700K	85	515	1387	No	
		W 3000K	85	608	1621	No	
		9W 3000K	90	545	1480	Yes	
		35 3500K	85	579	1569	No	
		C 4000K	85	601	1611	No	
	F 45°	27 2700K	85	542	756	No	
		W 3000K	85	635	865	No	
		9W 3000K	90	574	807	Yes	
		35 3500K	85	610	858	No	
		C 4000K	85	623	884	No	

HR-2LED-T509



Example: HR-2LED-T509F-9W-BN

COMPATIBLE HOUSINGS See individual housing spec sheets for complete information.

Model	Input	Notes
HR-2LED-H09D-ICA	120V -277V	Ceiling thickness: ½" -¾"
HR-2LED-H09D-ICAC		
HR-2LED-R09D-A	120V -277V	Does not accommodate adjustments for T309, T409, T509 Requires 3" of clearance from insulation on all sides Ceiling thickness: ½" -1"

REPLACEMENT MODULES

Reflectors

Spot	SL-REF-LUX10-S
Narrow Flood	SL-REF-LUX10-N
Flood	SL-REF-LUX10-F

LED

2700K	85 CRI	LXS8-PW27
3000K	85 CRI	LXS8-PW30
3000K	90 CRI	LXS9-PW30
3500K	85 CRI	LXS8-PW35
4000K	85 CRI	LXS8-PW40

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760