

Project: _____

Fixture Type: _____

Location: _____

Contact: _____

LED FLUSH

Ceiling mounted • Wet location listed



Specifications:

Description:

The all-in-one LED Surface Mount uses an intuitive snap-in system that allows easy flush mount installation to a junction box. 5-1/2" round with decorative glass ring. 3000K, 690 lumens, 90+ CRI. Dimming with many TRIAC dimmers. Wet location listed.

Construction:

Black (-31)
Steel construction
Glass: White polycarbonate lens
Flicker-free dimming to 10% brightness with most ELV type dimmers
(See Dimming Notes)
Title 24 compliant
covers a standard 4" hexagonal recessed outlet box
Mounting strap for outlet box included
6" of wire supplied
Black finish
Flicker free dimming down to 10%
Intuitive snap-in system

Performance:

Number of Modules	1
Input Power	10.5W
Input Voltage	
Input Frequency	
Lumens/LPW	690/66 (LM-79) per module
CCT	3000K
CRI	
Life	(L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Labels	cCSAus Wet location listed ENERGY STAR® qualified

Images:



Dimensions:

Diameter: 5-1/2"

Height: 1-1/2"

Catalog number:

Base

Finish

31 - Black

Color Temp

30K - 3000K

CRI

Blank- 90 CRI