



Please read this installation and maintenance guide in its entirety before removing vanity top from box and installing.

CAUTION

THIS VANITY TOP IS HEAVY. WE RECOMMEND TWO PEOPLE FOR LIFTING AND INSTALLATION.

This box contains the following:

1 (One) marble vanity top with attached porcelain bowl

1 (One) - 4" loose backsplash

1 (One) Installation & Maintenance Guide

MSI

Making Dream Surfaces Attainable



Engineered Marble
Vanity Installation &
Maintenance Guide

INSTALLATION INSTRUCTIONS

Your marble vanity top is an engineered product. Every vanity has its own unique characteristics, such as veining and coloration. Be sure to fully inspect your top for satisfaction before installation.

If you are not satisfied with your purchase or your vanity top is damaged, please contact Customer Care

Tools Needed:

Caulking gun
Silicone sealer
Caulking adhesive



- 1 Prepare and level the vanity cabinet and secure it to the wall. Use additional interior supports if the vanity is frameless or does not have full support around the frame. Additional wood supports should be 1" x 2" and affixed to the sides with caulking adhesive and short wood screws that do not protrude through any exposed sides.

Be sure to follow the recommended instructions for installation from your vanity cabinet manufacturer.

Helpful Hint #1: Before attaching to vanity cabinet, hand-tighten nuts on the bottom of your vanity top that may have loosened during shipping.

- 2 Apply a bead of silicone sealer on the top edges of the vanity cabinet. Place your vanity top on it with an overhang of 1/2" on the edges and permit the sealer to dry.

See manufacturer's instructions for drying time.



- 3 Be sure the wall is clean, dry and smooth. Remove loose paint or any wallpaper or decorative material before installation of the back splash. Apply two beads of caulking on the rear of the back splash and push firmly to the wall. You may have to use a patching compound if your wall is uneven or has holes or indentations.

Helpful Hint #2: The pre-drilled holes will accommodate most faucets; however we recommend you check to see that your faucet will work properly. Check to make sure the spout is long enough to extend out over the bowl.

- 4 Install the faucet system and the drain plumbing system. Using your hand, tighten the drainpipe connection to the bottom of the bowl. **DO NOT USE A WRENCH.** Tightening by wrench can result in damage to the bowl.

Follow the manufacturer's instructions for installing the faucet and drain.

CARE & MAINTENANCE

Maintaining marble is simple and easy. Just follow the care and maintenance below.

- For everyday cleaning use a damp cloth, sponge or paper towel.
- For more difficult stains use mild soap. For the most stubborn stains you can use a neutral pH cleaner and a nonabrasive scrub pad.
- Before applying any cleaning agent, be certain to rinse all of the surface area thoroughly.
- Sealing of the product is recommended on an annual basis for protection and durability. It is advisable to use a marble sealer.
- Follow the instructions of the Sealer's manufacturer.

GENERAL PRECAUTIONS

- Be cautious when exposing your marble surface to any household chemicals or solvents.
- Do not expose marble surfaces to any chemicals that contain trichlorethane, hydrofluoric acid or methylene chloride - such as paint remover or furniture strippers. These types of chemicals may etch or discolor the surface.
- It is recommended to use cleaning product that contains neutral pH content
- In case of an accidental exposure to products, thoroughly rinse the affected area with water as soon as possible
- In following these simple care and maintenance guidelines your vanity will provide you with many years of trouble-free use.

Helpful Hint #3: Any spill should be cleaned as soon as possible. Blot spills with a paper towel or clean rag as wiping a spill may spread the stain.