

**THANK YOU  
FOR YOUR PURCHASE!**

**Vinyl Wall Art Quotes  
& Prints**

DO NOT APPLY IN COLD WEATHER (BELOW 50 DEGREES) VINYL BECOMES BRITTLE  
DO NOT APPLY IN EXTREME HEAT (ABOVE 90 DEGREES)  
VINYL BECOMES SOFT AND STRETCHY  
DO NOT USE RUBBING ALCOHOL TO APPLY - IT DESTROYS THE ADHESIVE  
DO NOT TOUCH THE ADHESIVE BACKING OF THE DECAL  
DO NOT BE ALARMED IF YOUR DECAL CAME IN TWO PARTS.  
IN MANY CASES THE DECAL IS EASIER TO MANAGE WHEN IT NOT SO BIG

## HOW TO APPLY

### 1. CLEAN:

WIPE THE SURFACE YOU ARE APPLYING THE DECAL TO WITH A DAMP CLOTH (WATER ONLY). DRY BEFORE APPLYING .

### 2. MEASURE AND LEVEL:

DETERMINE THE DESIRED LOCATION AND MEASURE FOR PLACEMENT USING A LEVEL. MAKE SURE THE DECAL IS LEVEL AND POSITIONED SYMMETRICALLY.

### 3. SECURE WITH TAPE:

WHILE STILL HOLDING THE LEVELED POSITION, PLACE A FEW PIECES OF TAPE AT THE TOP OF YOUR DECAL.

### 4. TAPE IN PLACE:

APPLY ANOTHER PIECE OF TAPE (HORIZONTALLY) ACROSS THE TOP OF THE VINYL GRAPHIC.

### 5. REMOVE BACKING PAPER:





WITH THE TAPE FUNCTIONING AS A HINGE, FLIP THE VINYL OVER AND CAREFULLY REMOVE THE BACKING PAPER FROM THE GRAPHIC.

### 6. APPLY THE GRAPHIC

SLOWLY LOWER THE GRAPHIC IN PLACE APPLYING PRESSURE USING A CREDIT CARD. WORKING FROM THE CENTER OF THE GRAPHIC TO THE EDGE.

### 7. REMOVE TRANSFER TAPE

CAREFULLY AND SLOWLY PEEL AWAY THE TRANSFER TAPE AT A 45 DEGREE DOWNWARD ANGLE.



## DECAL REMOVAL

GO OVER THE DECAL AREA WITH A BLOW DRYER ON LOW HEAT FOR APPROXIMATELY 30-60 SECONDS. THIS SOFTENS THE ADHESIVE BACKING ON THE DECAL AND MAKES IT PLYABLE AND EASY TO REMOVE

