



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-1250 - 25/20/15 Watt LED Flood Light; 3K/4K/5K CCT; NEMA 4;
Bronze Finish; 120-347 Volt

- Wattage Selectable
- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	25W/20W/15W
Volts:	120V-347V
Lumens:	3000L/2400L/1800L
Lamp Base :	Integrated - Integrated
CRI:	70
CCT (Kelvins):	30K/40K/50K - Soft White to Natural Light
Beam Spread :	40/60/75
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 0-10V Dimming
Dimmable Down To %:	100 to 10 percent
Dimming Type :	0-10V Dimming
Incandescent Equivalent :	150W-200W
HID Equivalent :	100W-150W
Operating Temperature :	-40F to +113F (-40C to +45C)
Lamp Included :	Integrated
Replaceable Light Source :	No
Surge Protection :	Built-in surge protection - 4KV
THD:	<20%
Power Factor :	>0.9
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923413506
Each Quantity:	1
Each Dimensions:	8.03 x 5.20 x 5.20

INFO

Specification Note:	Default Wattage: 25W; 4Vx4H/5Vx5H/6Vx6H Beam Selectable
Integrated Features:	Integrated Photocell

PHYSICAL

Finish:	Bronze
Lens Material:	Polycarbonate (PC)
Dimensions:	L:7.71" W:4.82" H:4.92"
Weight (Lbs.):	1.32
Material:	Die-Cast Aluminum
Sensor:	Yes - Bypassable

COMPLIANCE

Safety Listing:	cETLus
Location Rating:	Wet
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-0SG3L3
CA Prop 65:	Lead
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK10
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions