



The Lakra | 44mm Log Cabin - Technical Data Sheet




- Superior Grade 44mm Finish Interlocking Logs
- Versatile Outdoor Shelter Section
- Quality Joiner Made Opening Window
- FREE Toughened Glazed Doors & Windows
- Heavy Duty 19mm T&G Roof and Floor

Cladding Material	Heavy Duty Interlocking T&G Logs	Cladding Thickness	44
Framing Style	Tanalised Bearers Only	Framing Size	58mm x 44mm
Roof Material	Tongue & Groove Board	Roof Thickness	19mm
Floor Material	Tongue & Groove Board	Floor Size	19mm
Door Style	Fully Glazed Joiner Made Double Doors	Door Size	1520mm x 1880mm
Window Style	Joiner Made Full Length Opening Windows	Window Size	645mm x 1378mm
Glazing Thickness	4	Glazing Material	Toughened Glass
Roof Covering	Black Mineral Felt	Treatment	Untreated
Locking System	3 Lever Lock with Brass Handles	Material	Selected European Softwoods


16x10:




18x10:



16x12:



18x12:



Building Dimension	Length	Width	Base Size	Internal Size	External Ridge	External Eaves	Internal Ridge	Internal Eaves	Ext. Size exc. Roof	Ext. Size inc. Roof	No. of Windows	Weight
16x10 Lakra	4750mm	2950mm	4560mm x 2760mm	4472mm x 2672mm	2438mm	2189mm	2346mm	2126mm	4750mm x 2950mm	4950mm x 3150mm	2	1049kgs
18x10 Lakra	5350mm	2950mm	5160mm x 2760mm	5072mm x 2672mm	2438mm	2189mm	2346mm	2126mm	5350mm x 2950mm	5550mm x 3150mm	2	1151kgs
16x12 Lakra	4750mm	3550mm	4560mm x 3360mm	4472mm x 3272mm	2438mm	2189mm	2346mm	2126mm	4750mm x 3550mm	4950mm x 3750mm	2	1183kgs
18x12 Lakra	5350mm	3550mm	5160mm x 3360mm	5072mm x 3272mm	2438mm	2189mm	2346mm	2126mm	5350mm x 3550mm	5550mm x 3750mm	2	1265kgs