
Important: Always disconnect the power before installing or replacing bulbs and before cleaning or other maintenance.

This light should be installed by a licensed electrician

CAUTION: Do not touch or apply pressure to the LEDs, or damage will occur. LAMP INSTALLATION AND ASSEMBLY

- 1. Shut off power to the outlet box. (fig. A)
- 2. Place fixture on a surface with the LEDs facing up. Place glass on extrusion tube and attach by inserting the two end caps into the extrusion tube and securing with countersunk screws.
- 3. Make appropriate electrical connections using wire nuts:
 - a. Connect the transformer's live wire (black) to the live outlet box wire.
 - b. Connect the transformer's neutral wire (white) to the neutral outlet box wire.
 - c. Connect fixture's ground wire (green or uncoated) to the ground outlet box wire. If no ground is present in outlet box, connect fixture's ground wire to the mounting plate using the green screw (included).
 - d. Carefully place connections and transformer in outlet box.
- 4. Attach mounting plate to the outlet box, secure with outlet box screws.
- 5. Install the back plate to the mounting plate by hooking the tab inside the back plate behind the small tab on the mounting plate, then tipping the back plate against the wall (fig. B). Use Allen key (included) to tighten the set screw against the large tab to secure.
- 6. Restore power to the fixture.

NOTE: This fixture is dimmable with Electronic Low Voltage (Trailing-Edge) type dimmers only.



CARE INSTRUCTIONS Dusting — Use a clean, dry cloth. Cleaning — To protect the finish, avoid any harsh abrasives or chemicals.

outlet box

