

Project:

Fixture Type: Location:

Contact:

# **PE2EU SERIES**

LED Emergency Light	
---------------------	--

## Specifications:

#### **Description:**

The PE2EU Series offers quality and value with a compact and attractive LED based emergency light. The white housing and lamp-heads are fully adjustable and glare-free. Snap together design for quick and easy installation with option of Wall or Ceiling mount. Remote capacity unit will run a double-head remote or 2 single-head remotes of the PERHC Series.

#### Features:

- LED life-cycle of more than 10 years
- Quick Installation
- Dual-voltage 120 or 277V AC input
- Includes long-life Nickel Cadmium battery for UL recognized 90 minute emergency lighting
- Remote capacity or extended runtime option
- Damp Location Listed
- Fully adjustable lamp-heads
- · Provided with test switch and AC-On indicator
- Wall or Ceiling mount
- 3 VDC
- 1 Watt

#### Application:

The PE2EU Series can be applied in stairwells, hallways, offices and other commercial applications.

#### **Energy Consumption:**

	120 VAC	277 VAC
PE2EU-30	0.56W	1W
PE2EU-30-RC	0.92W	1.62W
Accessories:		
<ul> <li>PERHC - SG - ID - 30</li> <li>PERHC - DB - ID - 30</li> <li>PERHC - SG - OD - 30</li> <li>PERHC - DB - OD - 30</li> </ul>	SG-ID	SG-OD
	DB-ID	DB-OD

#### Catalog number:

Base	Material	Input	Finish	Remote Capacity
PE2EU	Thermoplastic	120/277	<b>30</b> - White	RC - Remote Capacity

### Images:



#### **Dimensions:**



#### Warranty:

2 year full unit warranty

#### **Compliances:**

- UL924 Listed for Damp Location
  - NFPA 101 and NFPA 70
- OSHA

.