

Wall Mount Coverplate Fixture Installation and Wiring Instructions

NOTE: ALWAYS TURN POWER OFF BEFORE INSTALLING LIGHTING FIXTURES!

Installation (see Fig. A)

1. Disconnect power at main electrical panel before installation.
2. Pull **supply wires** through larger hole in **mounting plate** (hole has smooth edge).
3. Attach **mounting plate** to **outlet box** using **box screws** provided with **outlet box**. For additional stability on longer fixtures, install **mounting screws** into appropriate **fasteners** (**fasteners** not provided).
4. Follow wiring instructions carefully (listed below).
5. Position **coverplate** over **mounting plate**, aligning **studs** with **coverplate** holes and secure with **ballnuts**.

Wiring (see Fig. B)

1. Split the conductors of the **fixture wire** about 4 inches. Being careful not to expose any of the wire inside of the insulation.
2. Connect the **fixture ground wire** to the **outlet box ground wire** using **wirenut** (not provided). Connect **outlet box ground wire** to **mounting plate** with **GREEN** hex-head **ground screw** to tapped hole in **mounting plate** marked "GND".
3. Connect the half of the **fixture wire** that is white, marked, or has a ribbed surface to the **outlet box supply wire** (WHITE). Connect the other half of the **fixture wire** that is black, unmarked, or has a smooth surface to the **outlet box supply wire** (BLACK or RED). Use **wirenuts** provided.




Fig. A

Grounding Detail

Connect Black or Red House Wire to:	Connect White House Wire to:
Black	White
Parallel cord - SPT I & II (round & smooth)	Parallel cord - SPT I & II (square & ridged)
Clear, Brown, Gold or Black (without tracer)	Clear, Brown, Gold or Black (with tracer)
Insulated Wire (Other than GREEN) with copper conductor	Insulated Wire (Other than GREEN) with silver conductor

Fig. B