SDQ STAUNCH Lighting

ASSEMBLY AND INSTALLATION INSTRUCTIONS


Item No: VL39301SB

WARNING:TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTES:

1. Before installing,consult local electrical codes for wiring and grounding requirements.
2. Read and save these instructions.
3. Always switch off the electricity supply and allow to cool for 10 minutes before changing the light bulbs.

WALL LAMP



TOOLS REQUIRED




Flathead Screwdriver



Phillips Screwdriver




Ladder




Wire Strippers



Pliers



Electrical Tape



Wire Cutters



Safety Glasses

PREPARATION

Before beginning assembly of product, make sure all parts are present. Compare parts with package contents list and hardware contents list. If any part is missing or damaged, do not attempt to assemble the product.When the lamp is not installed finish,please don’t throw away the package,so as not to leave the parts in the package.


PART LIST AND HARDWARE LIST


PIECE	DESCRIPTION
A	Mounting plate
B	Green ground screw
C	Outlet box screw
D	Wire nut

PIECE	DESCRIPTION
E	Mounting screw
F	Fixture body
G	Acrylic shade

INSTALLATION

1. Attach the mounting plate(A) to the junction box with outlet box screw (C).
2. Attach the supply circuit ground wire (green or bare copper wire) to the the fixture ground wire, black to (black) and white to (white).
3. Attach the fixture body (F) to the mounting plate(A) with mounting screw(E).
4. Install the acrylic shades(G) to the fixture body (F) .
5. Adjust the color temperature by moving the 3CCT switch to be 3000K - 4000K - 5000K.





Thank you for purchasing a SDQ STAUNCH lighting product !
Need assistance with parts or assembly? Please call customer service at: 972-880-7868
Or visit us on-line at: WWW.SDQLIGHTING.COM or E-mail to:services@sdqlighting.com