Assembly Instructions



*Don't fully tighten all the bolts till the very end!

PRE-ASSEMBLY PREPARATION:
--- Please read through the instructions before beginning assembly.
--- Clear out the space for assembly and lay out all of the parts based on the Parts List, extra room will allow you to easily determine if all the pieces are present.
--- Keep small parts and pieces away from children until fully assembled.

Customer Support
For immediate assistance with shipping damages, missing components, or packaging issues, please contact our support team within 48 hours of delivery.
Email: HYDservice03@outlook.com
Service Hours: Mon - Fri

Part No.	Part	QTY	Image
A1	Left arm	1	
A2	Right arm	1	
C	Right front panel	1	
D	Left front panel	1	
E	Right back panel	1	

Part No.	Part	QTY	Image
F	Seat cushion	3	
K	Back cushion	3	
L	Bolt (M5*25mm)	4	
M	Bolt (M5*40mm)	24	
N	Washer M6	28	

Part No.	Part	QTY	Image
J	Left back panel	1	
G	Seat panel	2	
H	Seat middle panel	1	
I	Middle foot	1	

Part No.	Part	QTY	Image
O	Allen wrench	1	

Step 1: Attach front panels C&D with 2pcs bolts M and 2pcs washers N, using Allen wrench O. Note: Don't fully tighten the bolts.



M	螺栓	M5*40	2
N	垫圈	Φ16*Φ5.1*1.5	2

Step 2: Attach back E&F with 3pcs bolts M and 3pcs washers N, using Allen wrench O. Note: Don't fully tighten the bolts.



M	螺栓	M5*40	3
N	垫圈	Φ16*Φ5.1*1.5	3

Step 3: Attach arms A1&A2 to front panels C&D with 4pcs bolts M and 4pcs washers N, using Allen wrench O. Note: Don't fully tighten the bolts.

Attach arms A1&A2 to back panels E&F with 4pcs bolts M and 4pcs washers N, using Allen wrench O. Note: Don't fully tighten the bolts.



M	螺栓	M5*40	8
N	垫圈	Φ16*Φ5.1*1.5	8

Step 4: Attach seat panels G&H to front panels C&D with 4pcs bolts M and 4pcs washers N, using Allen wrench O. Note: Don't fully tighten the bolts.

Attach seat panels G&H to back panels E&F with 4pcs bolts M and 4pcs washers N, using Allen wrench O. Note: Don't fully tighten the bolts.



M	螺栓	M5*40	8
N	垫圈	Φ16*Φ5.1*1.5	8

Step 5: Attach middle foot I to middle seat panel H with 4pcs bolts L and 4pcs washers N, using Allen wrench O. Note: Please fully tighten all the bolts.



L	螺栓	M5*25	4
N	垫圈	Φ16*Φ5.1*1.5	4

Step 6: Put seat cushions J and back cushion K onto the seat . Assembly is now complete and the product is ready for use.

