


TigerFlex® Sunlit Pent Shed - Technical Data Sheet




- Windows and door can go in any position, on any side
- Well braced single door can be right or left hand hinged
- Toughened 3mm thick glass for durable finish
- Superior Grade 12mm Finish Shiplap T&G Cladding
- 28x44mm Finish Rounded Four Corner Framing
- 12mm Thick T&G Roof and Floor - **NO** OSB / Solid Sheet Board
- Unique and innovative design

Cladding Material	Shiplap	Cladding Thickness	12
Framing Style	Standard	Framing Size	28mm x 44mm
Roof Material	Tongue & Groove Board	Roof Thickness	12mm
Floor Material	Tongue & Groove Board	Floor Size	12mm
Door Style	Single Fully Boarded Tongue & Groove Door	Door Size	785mm x 1692mm
Window Style	All Fixed	Window Size	457mm x 610mm
Glazing Thickness	3	Glazing Material	Toughened Glass
Roof Covering	Black Mineral Felt	Treatment	TigerSkin® Burnt Orange (Water Based)
Locking System	Lock and Key + Turn Button	Material	Tongue & Groove Board


8x4:




12x4:



8x6:



12x6:



Building Dimension	Length	Width	Base Size	Internal Size	External Ridge	External Eaves	Internal Ridge	Internal Eaves	Ext. Size exc. Roof	Ext. Size inc. Roof	No. of Windows	Weight
8x4 TigerFlex® Sunlit Pent Shed	2388mm	1150mm	2388mm x 1150mm	2300mm x 1062mm	2030mm	1880mm	1950mm	1840mm	2412mm x 1174mm	2412mm x 1274mm	6	172kgs
12x4 TigerFlex® Sunlit Pent Shed	3538mm	1150mm	3538mm x 1150mm	3450mm x 1662mm	2030mm	1880mm	1950mm	1840mm	3562mm x 1174mm	3562mm x 1274mm	8	224kgs
8x6 TigerFlex® Sunlit Pent Shed	2388mm	1750mm	2388mm x 1750mm	2300mm x 1662mm	2030mm	1880mm	1950mm	1840mm	2412mm x 1774mm	2412mm x 1874mm	6	221kgs
12x6 TigerFlex® Sunlit Pent Shed	3538mm	1750mm	3538mm x 1750mm	3450mm x 1662mm	2030mm	1880mm	1950mm	1840mm	3562mm x 1774mm	3562mm x 1874mm	8	298kgs